
OMNITRONIC Wall-mounting bracket

- Suitable for Satellite-System
- For wall or ceiling installation
- Horizontal rotation 360°

No. 11229539

Technical specifications:

| | |
|---------------------|--------------------|
| Material: | Black steel |
| Maximum load: | 5 kg |
| Dimensions (LxWxH): | 105 x 100 x 140 mm |
| Weight: | 0.4 kg |


OMNITRONIC Wall-mounting for speakers

Extremely stable fixation

- Wall-mounting for all speakers with flange

No. 60004610

Technical specifications:

| | |
|---------------------|---------------------------------|
| Material: | Steel |
| Maximum load: | 25 kg |
| Pin: | Diameter 35 mm Length 100 mm |
| Dimensions (WxDxH): | 90 x 510 x 470 mm |
| Weight: | 1.5 kg |


OMNITRONIC Wall-mounting N for speakers

Extremely stable fixation

- Wall-mounting for all speaker-systems with flange
- Horizontal and vertical inclination angle adjustable

No. 60004615

Technical specifications:

| | |
|---------------------|---------------------------------|
| Material: | Black steel |
| Maximum load: | 25 kg |
| Pin: | Diameter 35 mm Length 100 mm |
| Dimensions (WxDxH): | 115 x 520 x 520 mm |
| Weight: | 3 kg |


OMNITRONIC WH Wall-mounting 30 kg max


Extremely stable fixation

- With flange
- Movable and/or tiltable
- Black lacquered steel version
- Applicable for truss mounting

 No. 60004616 WH-1
 No. 60004617 WH-2

WH-1

WH-2


OMNITRONIC Wall-mounting XY for speakers

Extremely stable fixation

- Wall-mounting for all speaker-systems with flange
- Horizontal and vertical inclination angle adjustable
- Very stable version
- Clamp area between pin and slide: 130 to 255 mm

No. 60004620

Technical specifications:

| | |
|---------------------|--------------------|
| Material: | Black steel |
| Maximum load: | 25 kg |
| Dimensions (WxDxH): | 250 x 365 x 250 mm |
| Pin (DxL): | 35 x 100 mm |
| Clamp area: | 130 to 255 mm |
| Weight: | 2.3 kg |


OMNITRONIC Distance tube subwoofer/satellite

For a stable connection

- Max. load 35 kg
- Weight 0.7 kg

 No. 60004550 80 cm
 No. 60004552 100 cm
 No. 60004554 120 cm
 No. 60004558 M20

OMNITRONIC Distance tube subwoofer/satellite w crank

Variable distance tube

- Distance tube for installing a satellite on a subwoofer
- Variable distance can be adjusted
- Distance tube with M20 thread
- Max. load 35 kg

No. 60004559

Technical specifications:

| | |
|-------------------------|--------|
| Max. carrying capacity: | 35 kg |
| Minimum height: | 0.80 m |
| Maximum height: | 1.10 m |
| Weight: | 3 kg |


OMNITRONIC Distance tube subwoofer/satellite variabel

For a stable connection

- Distance tube for installing a satellite on a subwoofer
- Variable distance can be adjusted
- Max. load 18 kg

No. 60004560

Technical specifications:

| | |
|-------------------------|----------|
| Max. carrying capacity: | 30 kg |
| Max. Last (DIN15560): | 18 kg |
| Minimum height: | 0.90 m |
| Maximum height: | 1.40 m |
| Tube diameter: | 42/35 mm |
| Weight: | 1 kg |