



NEW

OMNITRONIC Table microphone arm TMA-1N

Table holder

- Height universally adjustable (43-106 cm)
- Incl. 5 meter XLR cable

No. 60006009



OMNITRONIC Table microphone arm TMA-1 bk

Table holder

- Height universally adjustable (43-105 cm)
- Incl. 6 meter XLR cable

No. 60006010



OMNITRONIC Table microphone arm TMA-2 bk

Table holder

- Height universally adjustable (43-105 cm)
- Incl. 5 meter XLR cable
- Incl. holder

No. 60006011



OMNITRONIC ML-1 Monitor stand

Desktop isolator stand for monitor speakers

- Desktop isolator stand with acoustic foam pads for monitor speakers
- The solution for acoustical decoupling monitor speaker and underground
- For eliminating resonances or vibrations

No. 60004510

No. 8070265R.....50 mm, 50x50 cm
No. 8070265T.....100 mm, 50x50 cm

OMNITRONIC Accoustic foam, pyramid



NEW

No. 8070250A.....10 mm
No. 8070250B.....15 mm
No. 8070250C.....20 mm
No. 8070250D.....30 mm
No. 8070250E.....40 mm
No. 8070250F.....50 mm

ACCESSORY Soft Foam 100x200cm



No. 6000450P.....170x300x40 mm
No. 6000450U.....170x300x40 mm 2x
No. 6000450R.....265x330x40 mm
No. 6000450V.....265x330x40 mm 2x

OMNITRONIC Isolator monitor speakers

Monitor speaker pads

- The solution for acoustical decoupling monitor speaker and underground
- For eliminating resonances or vibrations
- 2 parts, different inclination angles possible
- Dimensions (LxWxH): 170 x 300 x 40 mm



No. 6000450N.....stand flange
No. 6000450M.....M-20, stand flange

OMNITRONIC

Speaker system stand installation flange

Flange for speaker systems

- Assure a stable mounting in the speaker system



No. 6000628D

OMNITRONIC AS-01 Microphone absorber system

Microphone absorber system for studio and live applications

- Reduces unwanted room reflections
- Transportable
- Quick and easy attachment to any conventional stand



No. 6000628E

OMNITRONIC AS-02 Microphone absorber system

Microphone absorber system for studio and live applications

- Reduces unwanted room reflections
- Transportable
- Stand screw clamp for all conventional stands with standard 16 mm inside thread (5/8")