

NEW DMX USB RDM DMX RDM



No. 70064516

EUROLITE DMX Move Controller 512 PRO

DMX controller with FX generator for motions

- DMX controller for DMX light effect units such as moving heads, scanners and LED spot lights with RGBW color mixture
- 512 DMX channels can be assigned and inverted as desired to 34 control channels (softpatch)
- For 24 fixtures with 34 control channels each
- 8 motorized DMX channel faders for user-friendly control
- Color-illuminated buttons provide easy orientation
- USB port for storing program data and firmware update
- Several movement patterns and color effects can be used simultaneously
- 30 programmable scenes
- 3 DMX fixture levels can be controlled

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
Number of control channels:	512
Storable scenes:	30
Storable chases:	30 with 100 steps each
DMX512/RDM output:	3-pin XLR connector
Available storage media:	USB devices (FAT32)
Dimensions (LxWxH):	483 x 170 x 107 mm
	Rack installation with 3 U
Weight:	3.9 kg

DMX USB RDM

EUROLITE DMX Move Controller 512

DMX controller with FX generator for motions

- 512 DMX channels can be assigned and inverted as desired to 32 control channels (softpatch)
- USB port for storing program data and firmware update
- Quick programming thanks to 9 integrated movement patterns and 7 color effects (PAN/TILT position, fade time and running time adjustable)
- 32 programmable chases with 100 scenes each can be stored
- 32 programmable scenes



No. 70064515

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz ~
	via power unit included in the delivery
Power consumption:	2.7 W
Number of control channels:	512
Storable scenes:	32
Storable chases:	32 with 100 steps each
DMX512/RDM output:	3-pin XLR connector
Available storage media:	USB devices (FAT32)
Dimensions (LxWxH):	483 x 130 x 82 mm
	Rack installation with 3 U
Weight:	2.2 kg



DMX RDM USB

FUTURELIGHT RDM PC Director USB Interface

Compact RDM interface

- USB interface and PC software for RDM-compliant DMX fixtures
- Quick analysis and configuration of fixture parameters
- 1 DMX universe



No. 51834860

Technical specifications:

Power supply:	230 V AC, 50 Hz ~
	via 12 V DC, 1 A power unit included in the delivery
Power consumption:	12 W
Number of control channels:	512
DMX512/RDM connectors:	3-pin XLR
USB port:	2.0, type B
Dimensions (LxHxD):	80 x 43 x 50 mm
Weight:	200 g



DMX USB PC connect

EUROLITE Pro Control DMX Software 1024

DMX control software Pro Control

- Popular lighting control software with advanced features for LJs, VJs, and lighting professionals
- 2 x software incl. USB interface (Pro Control + LED PC-Control)
- For 2 DMX universes (1024 channels), USB interface included in the delivery
- Supports Windows 7+8+10, Mac OS X and Linux
- Free SmartBoard DMX App available at the App store for Android and IOS



No. 51860116

