



100V IP44

OMNITRONIC HS-80 PA horn speaker

Horn speaker

- 2-way horn speaker for 100 V operation
- 4 power taps (10 W, 20 W, 40 W, 80 W)
- 16.5 cm woofer (6.5") and 2.5 cm tweeter (1")
- PTC tweeter protection
- High sound pressure and wide frequency range
- Weather-proof plastic housing (IP 44)

No. 80710828

Technical specifications:

Input voltage:	100 V
Components:	16.5 cm woofer (6.5") and 2.5 cm tweeter (1")
Rated power:	10 W RMS (green), 20 W RMS (white), 40 W RMS (yellow) 80 W RMS (red), COM (black)
Sensitivity (1 W/ 1 m):	99 dB
Frequency range:	90 Hz - 20 kHz
Protection rating:	IP 44
Dimensions (H x W x D):	348 x 348 x 288 mm
Weight:	5.3 kg



IP44 100V

OMNITRONIC HR PA horn speaker

Horn speaker

- High sound pressure and wide frequency range
- In weather-proof aluminum housing (IP 44)
- Locking possibility at the mounting bracket

No. 80710830HR-15

No. 80710832HR-20

No. 80710834HR-25

Technical specifications:

Device:	HR-15	HR-20	HR-25
Input voltage:	100 V	100 V	100 V
Rated power:	7.5 W, 15 W RMS	10 W, 20 W RMS	12.5 W, 25 W RMS
Sensitivity (1 W/ 1 m):	100 dB	102 dB	105 dB
Frequency range:	400 Hz - 5 kHz	400 Hz - 5 kHz	400 Hz - 5 kHz
Protection rating:	IP 44	IP 44	IP 44
Dimensions (D x D):	205 x 268 mm	204 x 305 mm	305 x 347 mm
Weight:	1.5 kg	1.7 kg	2 kg



4/8 ohm IP44

OMNITRONIC WF Flush-mount speaker

Flush-mount speaker

- 2-way coaxial speaker
- With 10 cm woofer (4") and 2.5 cm tweeter (1")
- Splash-proof (IP 44) construction for outdoor use

No. 80710863WF-4

No. 80710864WF-5

No. 80710865WF-6

Technical specifications:

Device:	WF-4	WF-5	WF-6
Rated power:	20 W RMS	25 W RMS	25 W RMS
Program power:	40 W	45 W	45 W
Components:	10 cm woofer (4"), 2.5 cm tweeter (1")	13 cm woofer (5"), 2.5 cm tweeter (1")	15 cm woofer (6"), 2.5 cm tweeter (1")
Connections:	2-pin terminal	2-pin terminal	2-pin terminal
Sensitivity (1 W/m):	88 dB, ±3 dB	90 dB, ±3 dB	90 dB, ±3 dB
Impedance:	8 ohms	8 ohms	8 ohms
Frequency range:	155 Hz - 20 kHz	95 Hz - 20 kHz	95 Hz - 20 kHz
Dimensions (HxWxD):	141 x 141 x 70 mm	165 x 165 x 75 mm	190 x 190 x 90 mm
Mounting cutout:	120 mm ø	140 mm ø	164 mm ø
Mounting depth:	53 mm	60 mm	65 mm
Weight:	0.4 kg	0.7 kg	0.8 kg



IP44 100V

OMNITRONIC GSG Garden speaker

Garden loudspeaker

- 2-way coaxial system
- 100 V transformer
- Weatherproof, green plastic housing (IP 44)
- For outdoor amplifying systems

No. 80710848GSG

No. 80710849GSG-30

Technical specifications:

Device:	GSG	GSG-30
Input voltage:	100 V	100 V
Components:	10 cm speaker (4")	15 cm speaker (6")
Rated power:	10 W RMS (green), 20 W RMS (white), COM (black)	7.5 W RMS (green), 15 W RMS (yellow), 30 W RMS (red), COM (blue)
Sensitivity (1 W/ 1 m):	95 dB, ±3 dB	90 dB, ±3 dB
Frequency range:	80 Hz - 15 kHz	80 Hz - 20 kHz
Dimensions (H x W x D):	215 x 215 x 245 mm	325 x 325 x 340 mm
Weight:	2.1 kg	3 kg