









PAR 30

OT*Q75PAR30 240V E27 30DEG GE BX1/15

40361

Product information

Halogen PAR lamps are a range of direct replacement for standard incandescent reflector lamps. They run on mains voltage, so you no longer need transformers or extra wiring to enjoy the crisp white light of halogen.

Application areas











Product data

Cap/Base	E27
Bulb Shape	PAR
Bulb Diameter [mm]	97
Maximum Overall Length [mm]	88
Net weight per piece [g]	143
Gross weight per piece [g]	220
Brand	General Electric (GE)

Performance data

Colour Rendering Index (CRI) [Ra]	100
Nominal correlated colour temperature (CCT) [K]	2900
Nominal beam angle [°]	30
Rated beam angle [°]	30
Nominal center beam candlepower (CBCP) [cd]	2200
Rated peak intensity in [Cd]	2200
Rated Lumens [lm]	650
Energy efficiency class (EEC)	D
Rated Life [h]	2000
Nominal Lifetime [h]	2000
Weighted energy consumption [kWh/1000h]	75.2





Electrical data

Nominal power [W]	75
Rated power [W]	75.0
Nominal lamp power factor	1
Nominal lamp voltage [V]	240
Run-up time (sec)	Instant startup
Starting time (sec)	0.0 s
Number of switching cycles	8000
Coil type	CC-8
Dimming Capability	Yes

Logistic data

Product status	Available
Outer case size	370 × 245 × 150 (mm)
Pallet quantity UK (PC)	1260
Pallet quantity EUR (PC)	945
Layer quantity UK	180
Layer quantity EUR	135
Layer quantity	135 EUR, 180 UK
Pack Quantity	15
EAN Code	0043168403610
DUN Code	10043168403617

Downloads & Links

Go to the catalog site (HTTP)

Halogen Lamps Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)