



GE
Lighting



PAR 36
4505 28.0V
24640

Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
 - Choice of beam widths
 - Excellent colour rendering
 - High efficiency combined with low operating costs
 - Robust and reliable
 - UV control
 - Easy retrofit
 - Colour consistent throughout life
 - Colour blends with halogen and fluorescent
-



Product data

| | |
|-----------------------------|-----------------------|
| Cap/Base | Screw terminal |
| Bulb Shape | PAR |
| Bulb Diameter [mm] | 114.3 |
| Maximum Overall Length [mm] | 70 |
| Net weight per piece [g] | 248 |
| Gross weight per piece [g] | 250 |
| Brand | General Electric (GE) |

Performance data

| | |
|---|-------|
| Nominal beam angle [°] | 15 |
| Nominal center beam candlepower (CBCP) [cd] | 45000 |
| Nominal power [W] | 50 |
| Nominal lamp voltage [V] | 28 |

Electrical data

| | |
|------------------|------|
| Lamp Current [A] | 1.79 |
| Coil type | CC-6 |
| Ballast Required | Yes |

Logistic data

| | |
|-------------------------|----------------------|
| DUN Code | 00043168246408 |
| Pack Quantity | 12 |
| Layer quantity | 1 UK |
| Layer quantity UK | 1 |
| Pallet quantity UK (PC) | 1200 |
| Outer case size | 226 x 211 x 313 (mm) |
| Product status | Available |

Application areas



Club and Disco

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

Disclaimer

Special Purpose Lamp, Not suited for household illumination