



GE
Lighting



PAR 36 4505 28.0V 24640

Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent

Application areas



Club and Disco



WORLDWIDE PARTNER

Product data

Cap/Base	Screw terminal
Bulb Shape	PAR
Bulb Diameter [mm]	114.3
Maximum Overall Length [mm]	70
Net weight per piece [g]	248
Gross weight per piece [g]	250
Brand	General Electric (GE)

Performance data

Nominal beam angle [°]	15
Nominal center beam candlepower (CBCP) [cd]	45000

Electrical data

Nominal power [W]	50
Nominal lamp voltage [V]	28
Lamp Current [A]	1.79
Coil type	CC-6
Ballast Required	Yes

Logistic data

DUN Code	00043168246408
Pack Quantity	12
Layer quantity	1 UK
Layer quantity UK	1
Pallet quantity UK (PC)	1200
Outer case size	226 x 211 x 313 (mm)
Product status	Available

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)

Disclaimer

Special Purpose Lamp, Not suited for household illumination