



GE  
Lighting



PAR 36

DWE Q650PAR36/1 120V

**41667**

---

## Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
  - Choice of beam widths
  - Excellent colour rendering
  - High efficiency combined with low operating costs
  - Robust and reliable
  - UV control
  - Easy retrofit
  - Colour consistent throughout life
  - Colour blends with halogen and fluorescent
- 



WORLDWIDE PARTNER

## Product data

Cap/Base	Screw terminal
Bulb Shape	PAR
Bulb Finish	Aluminized
Bulb Diameter [mm]	114.3
Maximum Overall Length [mm]	70
Net weight per piece [g]	230
Gross weight per piece [g]	255
Brand	General Electric (GE)
Energy efficiency class (EEC)	D

## Performance data

Nominal correlated colour temperature (CCT) [K]	3200
Nominal beam angle [°]	21
Nominal center beam candlepower (CBCP) [cd]	24000
Nominal lumens [lm]	1
Rated Life [h]	100
Nominal power [W]	650
Weighted energy consumption [kWh/1000h]	692.4
Nominal lamp voltage [V]	120

## Electrical data

Coil type	CC-6
Ballast Required	Yes

## Logistic data

DUN Code	00043168416672
EAN Code	0043168416672
Pack Quantity	12
Layer quantity	1 UK
Layer quantity UK	1
Pallet quantity UK (PC)	1200
Outer case size	226 x 211 x 313 (mm)
Product status	Available

## Application areas



Club and Disco

## Downloads & Links

[Go to the catalog site \(HTTP\)](#)

## Disclaimer

Special purpose lamp – Stage Studio. Not suitable for household illumination.