




PAR 64 FFR 120V **13228**

Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent

Application areas











Product data

Product Code	13228
Bulb Shape	PAR
Bulb Diameter [mm]	203.2
Maximum Overall Length [mm]	152.4
Net weight per piece [g]	945
Gross weight per piece [g]	1050
Brand	General Electric (GE)
Cap/Base	G16d

Performance data

Nominal beam angle [°]	21
Nominal center beam candlepower (CBCP) [cd]	125000
Weighted energy consumption [kWh/1000h]	1083.58
Energy efficiency class (EEC)	E
Rated Life [h]	800
Nominal correlated colour temperature (CCT) [K]]	3200
Nominal lumens [lm]	28000
Colour Rendering Index (CRI) [Ra]	100

Electrical data

Coil type	CC-6
Ballast Required	Yes
Nominal power [W]	1000
Nominal lamp voltage [V]	120





Logistic data

DUN Code	00043168132282
EAN Code	0043168132282
Pack Quantity	6
Layer quantity	1 UK
Layer quantity UK	1
Pallet quantity UK (PC)	252
Outer case size	197 x 354 x 551 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) High-res images / Technical drawings (HTTP) Certificate for the Quality Management System of GE Lighting EMEA (PDF) Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special purpose lamp – Stage Studio. Not suitable for household illumination.