



Halogen reflector

13163 250W GX5.3 24V 1CT/10X5F

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of **medical, projection and scientific illumination systems**. Their proven reliability makes them ideal for retrofit installations. **The burners** are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for **dental curing** applications. In addition, you get all the proven advantages of **halogen technology** such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. **Halogen lamps** also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.

Product data

General Information		Voltage (Nom)	
Cap-Base	GX5.3 [GX5.3]	24 V	
Philips Code	13163	Controls and Dimming	
ANSI Code	ELC	Dimmable	Yes
LIF Code	A1/259	Mechanical and Housing	
Bulb Shape	R50 [R 50mm]	Bulb Material	Quartz-UV Open
Operating Position	UNIVERSAL [Any or Universal (U)]	Reflector Finish	Smooth
Main Application	Projection	Filament Dimensions WxH	-
Life To 50% Failures (Nom)	50 h	Luminaire Design Requirements	
Light Technical		Bulb Temperature (Max)	900 °C
Correlated Color Temperature (Nom)	3400 K	Pinch Temperature (Max)	400 °C
Color Rendering Index (Nom)	100	Working Distance WD	32 mm
Operating and Electrical			
Power (Rated) (Nom)	250 W		


Halogen reflector

Product Data

Full product code	871150040975160
Order product name	13163 250W GX5.3 24V 1CT/10X5F
EAN/UPC - Product	8711500409751
Order code	923919720501
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	50
Material Nr. (12NC)	923919720501
Net Weight (Piece)	0.024 kg

Dimensional drawing



13163 250W GX5.3 24V

Product	D	C
13163 250W GX5.3 24V 1CT/10X5F	50 mm	44.5 mm

