











Single Ended Halogen T26 GCS 230- 240V

88463

Product information

Quartzline® lamps designed for optimum performance in today's precision range of stage, studio and architectural luminaires. Full range up to 24,000 W -Range of bases to meet the needs of OEMs -Chromised seal protection up to 500° C.

Application areas



Film and Broadcast



(F) Theatre









Product data

Cap/Base	GY9.5
Bulb Shape	Tubular
Bulb Diameter [mm]	25
Maximum Overall Length [mm]	88
Light Center Length [mm]	46
Net weight per piece [g]	25
Gross weight per piece [g]	35
Brand	General Electric (GE)

Performance data

Colour Rendering Index (CRI) [Ra]	100
Nominal correlated colour temperature (CCT) [K]	3050
Nominal lumens [lm]	15000
Energy efficiency class (EEC)	С
Rated Life [h]	400
Weighted energy consumption [kWh/1000h]	662.84

Electrical data

Nominal power [W]	650
Nominal lamp voltage [V]	240
Coil type	C-13
Dimming Capability	Yes
Ballast Required	No





Logistic data

Product status	Available
Outer case size	170 × 255 × 130 (mm)
Pallet quantity UK (PC)	4800
Pallet quantity EUR (PC)	4032
Layer quantity UK	600
Layer quantity EUR	504
Layer quantity	504 EUR, 600 UK
Pack Quantity	24
EAN Code	0043168884631
DUN Code	10043168884638

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination