



Single Ended Halogen ^{т13 гкв 230- 240v} **88497**

Product information

Quartzline® lamps designed for optimum performance in today's precision range of stage, studio and architectural luminaires. Full range up to 24,000 W -Range of bases to meet the needs of OEMs -Chromised seal protection up to 500° C.


Application areas



() Theatre











Product data

Light Center Length [mm]	55.5
Product Code	88497
Bulb Shape	Tubular
Bulb Diameter [mm]	25
Maximum Overall Length [mm]	121
Net weight per piece [g]	135
Gross weight per piece [g]	150
Brand	General Electric (GE)
Cap/Base	P28s-24

Performance data

Weighted energy consumption [kWh/1000h]	663.46
Energy efficiency class (EEC)	D
Rated Life [h]	750
Nominal correlated colour temperature (CCT) [K]]	3000
Nominal lumens [lm]	13500
Colour Rendering Index (CRI) [Ra]	100

Electrical data

Coil type	C-13
Dimming Capability	Yes
Ballast Required	No
Nominal power [W]	650
Nominal lamp voltage [V]	240





Logistic data

DUN Code	10043168884973
EAN Code	0043168884976
Pack Quantity	12
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	144 EUR, 180 UK
Layer quantity EUR	144
Layer quantity UK	180
Pallet quantity EUR (PC)	1152
Pallet quantity UK (PC)	1440
Outer case size	190 x 350 x 126 (mm)
Product status	Available

Downloads & Links Go to the catalog site (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) High-res images / Technical drawings (HTTP) Certificate for the Quality Management System of GE Lighting EMEA (PDF) Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination