



# Discharge - Single Ended Cold Start CSR700/2/SE 49491

# **Product information**

Compact, single ended metal halide cold start lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering Ra from 70 – 90+- High CCT 7200 -9000 K with superior colour stability -Universal burn position -Dimmable with stable colour- High efficiency with excellent lumen maintenance.


#### **Application areas**



Event and Tour











## Product data

Cap/Base	G22
Bulb Shape	Tubular
Bulb Finish	Clear
Bulb Diameter [mm]	28.6
Maximum Overall Length [mm]	155
Light Center Length [mm]	75
Arc Gap	7.5
Net weight per piece [g]	190
Gross weight per piece [g]	213
Operating position	U - Universal
Brand	General Electric (GE)

## Performance data

Colour Code	765
Colour Rendering Index (CRI) [Ra]	70
Nominal correlated colour temperature (CCT) [K]	6500
Nominal lumens [lm]	55000
Energy efficiency class (EEC)	A
Nominal chromaticity coordinate X	0.312
Nominal chromaticity coordinate Y	0.325
Weighted energy consumption [kWh/1000h]	770

### **Electrical data**

Nominal power [W]	700
Nominal lamp voltage [V]	70
Lamp Current [A]	10
Dimming Capability	No
Ballast Required	Yes





#### Logistic data

DUN Code	20043168494919
EAN Code	0043168494915
Pack Quantity	10
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	130 UK
Layer quantity UK	130
Pallet quantity UK (PC)	780
Outer case size	370 x 154 x 230 (mm)
Product status	Available

Downloads & Links Go to the catalog site (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) High-res images / Technical drawings (HTTP) Certificate for the Quality Management System of GE Lighting EMEA (PDF) Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

#### Disclaimer

Special Purpose Lamp, Not suited for household illumination