



Commercial Products & Solutions

 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)
[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)
[Products](#) > [High Intensity Discharge](#) > [Quartz Metal Halide](#) > [301 - 1000 Watts](#) > 15378
15378 – CSR575/2/SE

GE Quartz Metal Halide T9 - Stage & Studio


**GENERAL CHARACTERISTICS**

Lamp type	High Intensity Discharge - Quartz Metal Halide
Bulb	T9
Base	Prefocus Medium 2-Pin (GX9.5)
Wattage	575
Voltage	97
Rated Life (Vert)	1000 hrs
LEED-EB MR Credit	1327 picograms Hg per mean lumen hour
Primary Application	Stage & Studio

Bulb



Base

[View Larger](#)**ADDITIONAL RESOURCES**[Catalogs](#)[Testimonials](#)[MSDS \(Material Safety Data Sheets\)](#)[Disposal Policies & Recycling Information](#)**PHOTOMETRIC CHARACTERISTICS**

Initial Lumens	49000
Nominal Initial Lumens per Watt	85
Color Temperature	7200 K
Color Rendering Index (CRI)	80
CIE Color x	0.302
CIE Color y	0.32

ELECTRICAL CHARACTERISTICS

Burn Position	Universal burning position
---------------	----------------------------

DIMENSIONS

Maximum Overall Length (MOL)	4.9200 in (124.9 mm)
Light Center Length (LCL)	2.560 in (65.0 mm)

PRODUCT INFORMATION

Product Code	15378
Description	CSR575/2/SE
Standard Package	Case
Standard Package GTIN	10043168153789
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168153782

CAUTIONS & WARNINGS[See list of cautions & warnings.](#)[Return To Top](#)

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright 2009 General Electric Company