











Discharge - Double Ended Hot Restrike CSR1200/S/DE/60

22494

Product information

Double ended compact source rare earth metal halide hot restrike lamps from GE can be used in a variety of applications requiring high luminance, reliability and excellent colour characteristics. Industry Standard outline with hot restrike capability- Dimmable with stable colour- High efficiency with excellent lumen maintenance.

Application areas



Film and Broadcast



Event and Tour









Product data

SFc10-4
Globe
Clear
21
138
7
115
130
U - Universal
General Electric (GE)

Performance data

Colour Code	960
Colour Rendering Index (CRI) [Ra]	90
Nominal correlated colour temperature (CCT) [K]	6000
Nominal lumens [lm]	110000
Energy efficiency class (EEC)	A+
Nominal chromaticity coordinate X	0.323
Nominal chromaticity coordinate Y	0.325
Weighted energy consumption [kWh/1000h]	1320

Electrical data

Nominal power [W]	1200
Nominal lamp voltage [V]	100
Lamp Current [A]	12
Dimming Capability	No
Ballast Required	Yes



Discharge - Double Ended Hot Restrike CSR1200/S/DE/60

22494

Logistic data

DUN Code	10043168224946
EAN Code	0043168224949
Pack Quantity	10
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	260 EUR, 330 UK
Layer quantity EUR	260
Layer quantity UK	330
Pallet quantity EUR (PC)	1040
Pallet quantity UK (PC)	1320
Outer case size	208 x 166 x 230 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination