











Arcstream™ Double Ended Coloured

ARC150/UVC/TD/GREEN/RX7S-24

12181

Product information

High brightness, high quality white and coloured light with good colour rendition, excellent colour consistency and energy efficiency make these lamps suitable for retail environments and commercial interiors. Lamps with UVC feature are optimal for museum and retail environments where UV control is important.

Application areas



Retail



Industrial





Arcstream™ Double Ended Coloured ARC150/UVC/TD/GREEN/RX7S-24

12181

Product data

Rx7s
Double Ended
Clear
135.4
66
34
69
H45 - Horiz 45 degrees
15
Exempt
General Electric (GE)

Performance data

Nominal lumens [lm]	9000
Rated Lumens [lm]	9000
Nominal efficacy [LpW]	60
Rated efficacy [LpW]	60
Energy efficiency class (EEC)	В
Nominal chromaticity coordinate X	0.255
Nominal chromaticity coordinate Y	0.54
Weighted energy consumption [kWh/1000h]	165



Arcstream™ Double Ended Coloured ARC150/UVC/TD/GREEN/RX7S-24

12181

Electrical data

Nominal power [W]	150
Rated power [W]	150.0
Nominal lamp voltage [V]	95
Lamp Current [A]	1.8
Design Ambient Temperature [°C]	25
Run-up time (sec)	180
Hot restart time (sec)	600
Dimming Capability	Yes
Ballast Required	Yes

Logistic data

DUN Code	20043168121815
EAN Code	0043168121811
Pack Quantity	12
Layer quantity	408 EUR, 528 UK
Layer quantity EUR	408
Layer quantity UK	528
Pallet quantity EUR (PC)	1632
Pallet quantity UK (PC)	2112
Outer case size	178 x 138 x 221 (mm)
Product status	Available





Arcstream™ Double Ended Coloured ARC150/UVC/TD/GREEN/RX7S-24

12181

Downloads & Links

Go to the catalog site (HTTP)

HID Lamps Spectrum Catalogue (EN) (PDF)

Arcstream™ Double Ended Data sheet (EN) (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)