



Features:

EUROLITE STT-400/85 Winch Stand TÜV/GS

High-quality winch-stand, maximum load 85 kg, maximum height 400 cm

- 1-gear winch for easy lifting of the loads
- Automatic braking system
- Safety bolt for mechanical locking
- Easy handling
- Complies with DIN 15560-27 and DIN EN ISO 12100-2
- Adjustable height
- TÜV Süd certified

EUROLITE TAH-35M Truss Adapter, large

Adapter from 12 - 35 cm, maximum load WLL 300 kg

- Truss adapter for truss systems up to 55 mm diameter
- Adjustable clamps
- Adjustment between 120 mm and 350 mm
- LGA tested

ALUTRUS TRILOCK 6082-2000 3-way Cross Beam

3-point truss system

- Low weight
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified

Logistic

- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

| | |
|---------|----------|
| Weight: | 77.60 kg |
|---------|----------|

EUROLITE STT-400/85 Winch Stand TÜV/GS

| | |
|----------------------------|-------|
| Maximum carrying capacity: | 85 kg |
|----------------------------|-------|

| | |
|---------------|-------|
| Minimum load: | 25 kg |
|---------------|-------|

| | |
|-----------|----------------------------------|
| Standard: | DIN 15560-27, DIN EN ISO 12100-2 |
|-----------|----------------------------------|

| | |
|---------|---|
| Height: | Maximum: 400 cm above 3 sections Minimum: 175 cm |
|---------|---|

| | |
|--------------------|--------|
| Attachment system: | Ø 35mm |
|--------------------|--------|

| | |
|-------------|--------|
| Steel rope: | Ø 4 mm |
|-------------|--------|

| | |
|------------------------|---------------------|
| Type (general stands): | Light stand/wind up |
|------------------------|---------------------|

| | |
|-----------------------|------------------------|
| Transport dimensions: | 175 cm x 30 cm x 27 cm |
|-----------------------|------------------------|

| | |
|------------|----------|
| Base area: | Ø 160 cm |
|------------|----------|

| | |
|---------|----------|
| Weight: | 24.10 kg |
|---------|----------|

EUROLITE TAH-35M Truss Adapter, large

| | |
|-------------------------------|--------|
| Maximum load BGV C1 (8-fold): | 150 kg |
|-------------------------------|--------|

| | |
|----------------------------|--------|
| Maximum load WLL (4-fold): | 300 kg |
|----------------------------|--------|

| | |
|--------------------|--------|
| Attachment system: | Ø 35mm |
|--------------------|--------|

| | |
|------------------------|-----------|
| Type (general stands): | Accessory |
|------------------------|-----------|

| | |
|-----------|-------|
| Material: | Steel |
|-----------|-------|

| | |
|--------|----------------------------------|
| Width: | Maximum: 35 cm Minimum: 12 cm |
|--------|----------------------------------|

| | |
|-------------|--|
| Dimensions: | Width: 46 cm Depth: 7.50 cm Height: 22.50 cm |
|-------------|--|

| | |
|---------|---------|
| Weight: | 2.40 kg |
|---------|---------|

ALUTRUSS TRILOCK 6082-2000 3-way Cross Beam

| | |
|--------|-------------------|
| Setup: | Easy installation |
|--------|-------------------|

| | |
|------------|--------------|
| Trusspipe: | 50 mm x 2 mm |
|------------|--------------|

| | |
|--------------------|-------------|
| Welding technique: | TIG-welding |
|--------------------|-------------|

| | |
|-------------------|--------|
| Welding material: | AlMg 5 |
|-------------------|--------|

| | |
|--------|-------------|
| Color: | Alu colored |
|--------|-------------|

| | |
|-----------------------------|----------|
| Strut diameter x thickness: | 16 x 2mm |
|-----------------------------|----------|

| | |
|-------------|----------------|
| Dimensions: | Length: 200 cm |
|-------------|----------------|

Width: 29 cm
Height: 25.70 cm

Weight: 8.20 kg

Scope of delivery:

2 x EUROLITE STT-400/85 Winch Stand TÜV/GS

1 x user manual

2 x EUROLITE TAH-35M Truss Adapter, large

1 x adapter
2 x bolt
1 x user manual

3 x ALUTRUSS TRILOCK 6082-2000 3-way Cross Beam

1 x connection set