



Features:

EUROLITE LED Pixel Tube 360° clear 1m

DMX LED tube for truss installation or ceilings

- Lightweight plastic tube
- Beam angle 360°
- 16 individually controllable pixels (illumination units with 4 LED each)
- Stepless color blend, color change, dimmer and strobe effect
- Controllable via EUROLITE LED PSU-24V/10 DC controller; needed for operating the unit and not included in the delivery
- 10 LED Pixel Tubes 360° can be used with one controller
- For professional effect lighting in discotheques and on stages
- 64 LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
- Control via Art-Net; stand-alone; DMX

EUROLITE LED PSU-24V/10 DC LED Tube 360°

Controller for EUROLITE LED Pixel Tubes 360°

- Controller and power supply unit for 10 LED light tubes
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- Fixtures available for LED PC-Control 512
- 3 digit 7-segment LED display
- Mains input and output for power linking up to 8 units

Logistic

Technical specifications:

Weight:	8.91 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED Pixel Tube 360° clear 1m

Power supply:	24V DC
Power consumption:	20.00 W
Lamp type:	LED lamp
LED type:	64 x SMD 5050 3in1 TCL RGB (homogenous color mix)
Control:	Art-Net; stand-alone; DMX
Beam angle (1/2 peak):	360°
Dimensions:	Length: 103 cm Diameter: Ø 5 cm
Weight:	0.52 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED PSU-24V/10 DC LED Tube 360°

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	240.00 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	10 x 3-pin screw plug connector (F) IP 1 x IEC connector (F) mounting version
DMX channels:	5; 7; 23; 480
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function
Fixtures available for:	LED PC-Control 512
Display type:	3 digit 7-segment LED display
Output:	24 V DC, stabilized;
Dimensions:	Width: 29 cm Depth: 30 cm Height: 6 cm
Weight:	3.30 kg

OMNITRONIC XLR cable 3pin 10m bk/rd

Cable construction:	Audio cable
Cable length:	10 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Weight:	0.43 kg

Scope of delivery:

1 x XLR cable