



---

**Features:****OMNITRONIC LH-088 Cable Tester**

Universal cable tester for use in show technology

- Ideal cable test for all cable connections in the studio and for live applications
- Tests 3+5-pin XLR-, 3.5/6.3 mm jack (also stereo), Mini-DIN, DIN, RCA and 4+8-pin Speaker cables and connections
- Polarity and short-circuit display
- Comfortable selection via rotary switch
- Continuity tester via two banana sockets for connecting the measuring pins. LED and beeper indicate continuity
- A must for musicians and technicians
- Operation with 9 V battery

**OMNITRONIC LH-090 Polarity Tester System**

Accurate determination of polarity

- Set includes transmitter and receiver unit
- Easy and quick testing of speakers, amplifiers, microphones, etc.
- Receiver displays test result via two LEDs
- In and out via unbalanced jack sockets
- Acoustical and electrical output
- Adjustable input and output level
- Operation via 9 V battery each
- Powered by a battery/battery pack

---

**Logistic**

### OMNITRONIC LH-095 Speaker Checker

Speaker testing device with adjustable sinus frequency

- Quick and easy check of loudspeakers and sound systems - without assembling effort
- All you need is the LH-095 and a cable
- The optimum tool for sound engineers and Rental companies
- Adjustable sinus frequency 20 Hz - 20 KHz
- With spring bow and belt clip
- Powered by a battery/battery pack
- For application areas such as: Mobile use; mobile djs / entertainer

### OMNITRONIC SLM-500 SPL Meter

Digital sound level meter with A and C weighting

- Dedicated LCD
- Electret condenser microphone cartridge
- Measuring range from 30-130 dB
- Max Hold function
- A and C weighting
- Slow and fast measuring mode
- Additional outputs for AC and DC current via 3.5 mm jack (1/8")
- Operation via 4 x 1.5 V battery or 6 V power supply unit (both not included)
- Incl. windscreen and battery
- Powered by a battery/battery pack

### ROADINGER Universal Case FOAM GR-1 black, big

Carrying case

- With pickfoam
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 22mm with rounded edges
- Rugged carrying handle
- 2 chrome tip-over locks
- 2 high-quality spring locks with shut-off function
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Technical specifications:

---

Weight: 7.13 kg

---

### OMNITRONIC LH-088 Cable Tester

Battery: 1 x 9.0 V E block 6LR61 alkaline manganese included

---

Dimensions: Width: 14.5 cm  
Depth: 11 cm  
Height: 6 cm

---

Weight: 0.89 kg

---

### OMNITRONIC LH-090 Polarity Tester System

Battery: 1 x 9.0 V E block 6LR61 alkaline manganese included

---

Dimensions:	Width: 12.5 cm Depth: 5.5 cm Height: 3.2 cm
Weight:	0.22 kg
Power consumption:	5 mA
Audio connector:	6.3 mm unbalanced jack

#### OMNITRONIC LH-095 Speaker Checker

Output power:	1 W RMS (8 ohms)
Power connection:	Battery/battery pack included
Battery:	1 x 9.0 V E block 6F22 zinc carbon included
Frequency range:	20 - 20000 Hz variable
Control elements:	Level control
Connections:	Output: line via 1 x 3-pin XLR 2 V Speaker via 1 x speaker built-in socket (F) Speaker via 1 x screw terminal
Dimensions:	Width: 11.5 cm Depth: 9.5 cm Height: 4.5 cm
Weight:	0.43 kg

#### OMNITRONIC SLM-500 SPL Meter

Power connection:	Battery/battery pack
Battery:	4 x Mignon (AA) (not included)
Frequency range:	31.5 - 8500 Hz
Dimensions:	Width: 14.5 cm Depth: 6 cm Height: 11 cm
Weight:	0.68 kg
Power supply:	6 V AC/DC
via power unit:	max. 9 V DC, 100 mA
via battery:	4 x 1.5 V (type AA)
Battery life:	approx. 20 hrs.
Measuring ranges:	30-80 dB, 40-90 dB, 50-100 dB, 60-110 dB, 70-120 dB, 80-130 dB, 30-130 dB
Accuracy:	±1.5 dB @ 94 dB, 1kHz
Level weighting:	A or C
Microphone:	electret condenser microphone
AC output:	0.707 V RMS
Output impedance:	600 ohms
DC output:	10 mV
Output impedance:	100 ohms

#### ROADINGER Universal Case FOAM GR-1 black, big

Maximum load:	20 kg
Aluminum profile frames:	22 mm
Carrying handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Spring lock: 2 pc/pcs with shut-off function
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated
Inside dimensions:	48 cm x 38 cm x 11.5 cm
Dimensions:	Width: 52 cm Depth: 42 cm Height: 17 cm
Weight:	4.90 kg

### **Scope of delivery:**

---

1 x device  
1 x user manual  
1 x battery  
4 x foot