



**The article is no longer in our assortment.**

### Features:

#### EUROLITE LED Pixel Tube 360° clear 1.5m

DMX LED tube for truss installation or ceilings

- Lightweight plastic tube
- 26 individually controllable pixels (illumination units with 4 LED each)
- Stepless color blend, color change, dimmer and strobe effect
- 4 LED Pixel Tubes 360° can be used with one controller
- 104 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
- Control via Art-Net; stand-alone; DMX
- With a beam angle of 360°
- For application areas such as: Clubs/dancing school; stage

#### EUROLITE LED PSU-24V/4 DC LED Tube 360°

Controller for EUROLITE LED Pixel Tubes 360°

- Controller and power supply unit for 4 LED light tubes
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- Preprogrammed in LED PC-Control 512
- 3 digit 7-segment LED display

#### Package contents

- 1 x device, 1 x user manual, 1 x power cord

### Logistic

## Technical specifications:

### Legal specifications

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### EUROLITE LED Pixel Tube 360° clear 1.5m

Power supply:	24V DC
Power consumption:	18,00 W
LED type:	104 x SMD 5050 3in1 TCL RGB (homogenous color mix)
Control:	Art-Net; stand-alone; DMX
Beam angle:	360°
Beam angle (1/2 peak):	360°
Dimensions:	Length: 153 cm Diameter: Ø 5 cm
Weight:	0,70 kg

### Legal specifications

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### EUROLITE LED PSU-24V/4 DC LED Tube 360°

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	95,00 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
DMX channels:	5; 7; 14; 84; 192; 312
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function
Preprogrammed in:	LED PC-Control 512
Maximum connection:	4 tubes
Display type:	3 digit 7-segment LED display
Output:	24 V DC;
Dimensions:	Width: 24 cm Depth: 29 cm Height: 6 cm
Weight:	2,05 kg