



**The article is no longer in our assortment.**

### Features:

#### ALUTRUSS Base Plate BP-30 80x80

Baseplate for mobile use (connectors 6082 included)

- For the vertical installation of truss elements
- Multifunctional use
- High durability
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Trade fair and shop fitting; wedding/gala/events

### Logistic

#### ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### Package contents

- 1 x connection set

## **ALUTRUSS QUADLOCK End Plate QQGP**

Robust truss system

- High stability
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Easy installation as the cross-beams do no longer need to be screwed on
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school

## **ALUTRUSS QUADLOCK set connecting cone/pivot/pin**

QUADSYSTEM set

- Accessories for the robust truss system
- Trusspipe: 50 mm
- Made in Europe

## **EUROLITE CRT-120 LED-Curtain**

LED curtain with 120 LEDs RGB+yellow and compatible DMX controller (3 x 2 m)

- Several curtains can be linked via DMX512
- 120 powerful LEDs 5 mm R/G/B/A
- Dimmer electronic; color selection manual; color change adjustable; color fade adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone
- Easy installation
- Water repellent
- B1 low flammability
- For application areas such as: Party room; mobile djs / entertainer

### **Package contents**

- 1 x controller, 1 x curtain, 1 x user manual, 1 x power cord, 58 x mounting material, 8 x illuminant

## **ALUTRUSS SINGLELOCK POWER PSP-3000 QUICK-LOCK Pipe**

Single tube with QUICK-LOCK

- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- For decoration or frame construction for projection foils
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Trade fair construction; stage; rental

### **Package contents**

- 1 x connection set

## **EUROLITE TPC-56 Coupler Cone silver**

Coupler for 50 mm tube with Quicklock 6082 conical connector, maximum load WLL 500 kg

- With conical connector matching the Quicklock truss systems Singlelock, Bilock, Trilock 6082, Quadlock 6082

## **Technical specifications:**

---

Weight: 94,28 kg

---

#### Legal specifications

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### ALUTRUSS Base Plate BP-30 80x80

Trusspipe:	50 mm
Material:	Steel
Color:	Alu colored
Dimensions:	Width: 80 cm Depth: 80 cm Height: 0,60 cm
Weight:	28,60 kg

#### ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

Setup:	Easy installation
Trusspipe:	50 mm x 2 mm
Welding technique:	TIG-welding
Welding material:	AlMg 5
Alloy:	AlMgSi1 T6
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 200 cm Width: 29 cm Height: 29 cm
Weight:	10,80 kg

#### ALUTRUSS QUADLOCK End Plate QQGP

Setup:	Easy installation
Trusspipe:	50 mm
Color:	Alu colored
Weight:	2,05 kg

#### ALUTRUSS QUADLOCK set connecting cone/pivot/pin

Trusspipe:	50 mm
Color:	Alu colored
Weight:	0,96 kg

#### EUROLITE CRT-120 LED-Curtain

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15,00 W

IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
LED type:	120 x 5 mm R/G/B/A
Flash rate:	1 - 12 Hz
DMX channels:	8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone
Setup:	Easy installation
Housing color:	Black
Material:	, water repellent
Controller	
Dimensions:	Width: 18 cm Depth: 19 cm Height: 9 cm
Weight:	1,2 kg
Curtain	
Dimensions:	Width: 300 cm Height: 200 cm
Weight:	3,6 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### ALUTRUSS SINGLELOCK POWER PSP-3000 QUICK-LOCK Pipe

Setup:	Easy installation
Trusspipe:	50 mm x 3 mm
Welding technique:	TIG-welding
Welding material:	AlMg 5
Alloy:	AlMgSi 0.5
Color:	Alu colored
Dimensions:	Length: 300 cm
Weight:	3,95 kg

#### EUROLITE TPC-56 Coupler Cone silver

Maximum load BGV C1 (8-fold):	250 kg
Maximum load WLL (4-fold):	500 kg
Tube diameter sector:	45 - 50 mm
Material:	Aluminum
Color:	Silver

Dimensions:	Length: 13 cm
	Width: 5 cm
	Depth: 11,50 cm
Weight:	0,61 kg