



The article is no longer in our assortment.

Features:

EUROLITE PAR-64 Spot Long with Cable bk

Long PAR-64 housing (with open cable ends)

- Durable aluminum cabinet
- Strong aluminum mounting bracket
- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Blackened tube for precise light output
- Strong brass clamps with extension spring for safe hold and for quick opening of the rear housing cover
- Protection grille on the rear housing cover - complies with CE regulations
- Comes fully-wired with black silicone cable, stable earthing in the housing and directly clamped ceramic socket
- Color filter frame included in delivery
- Strong cable tension relief
- Well-suited for easy installation of our Raylight reflectors with matching connector (GX16)
- Simple mounting: connect with ceramic socket - ready!
- Power plug has to be ordered separately; delivery is with open cable ends; delivery is with open cable ends; delivery is with open cable ends; delivery is with open cable ends; delivery is with open cable ends
- For PAR 64

Package contents

- 1 x spotlight, 1 x filter frame, 1 x lamp clamping ring, 1 x user manual

Logistic

EUROLITE Raylight PAR-64,GY-9.5 Socket long

The alternative to traditional lamps

- Immediately and without changing the wiring, exchangeable by flanged on pin socket (GX 16) against a PAR-64 lamp
- Cost savings, as only the burner must be replaced at a lamp change
- Longlife lamp types (up to 2.000 h) also save time and money
- Low weight

OMNILUX A1 230V/500W GY-9.5 75h

Special lamp for show effect lighting

- One-sided base
- Easy lamp replacement
- Dimmable
- Very high color rendering index (CRI)

Technical specifications:

Weight:	2,13 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE PAR-64 Spot Long with Cable bk

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 1000 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0,7 m
Base:	GX16d
Lamp type:	Selectable
Color generation:	Via color filter frame (optional)
Housing color:	Black
Slot for spot length:	25,7 cm x 25,7 cm
Dimensions:	Length: 42,5 cm Width: 26,5 cm Height: 27 cm
Weight:	1,97 kg
Filter frame	
Dimensions:	Length: 25,5 cm Width: 25,5 cm Diameter: Ø 20,2 cm
Legal specifications	
Special product:	Not designed for household room illumination

Intended use:	Show effect lighting
---------------	----------------------

EUROLITE Raylight PAR-64,GY-9.5 Socket long

Power supply:	230 V AC, 50 Hz
Power consumption:	500 W
Base:	GY9.5; GX16d
Beam angle (1/2 peak):	NSP
Color:	Alu colored
Dimensions:	Diameter: Ø 20,3 cm
Weight:	0,14 kg

OMNILUX A1 230V/500W GY-9.5 75h

Voltage (lamps):	230 V, AC
Nominal wattage:	500 W
Base:	GY9.5
Lamp type:	Halogen lamp
Lamp specification:	Dimmable
Beam angle:	310°
Color of light:	White
Color temperature:	2700K
Color rendering index (CRI):	100 Ra
Lead time:	0,2 s
Construction:	Bi pin
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	75 h
Luminous flux:	7200 lm
Wavelength:	778 nm
Lamp current:	2,17 A
Dimensions (LxD):	78x18 mm
Weight:	0,02 kg
Energy efficiency class (A - G):	G
EPREL-Nr:	1519666