



The article is no longer in our assortment.

Features:**OMNITRONIC ADI-004M Interface**

USB audio interface with integrated low-noise microphone preamplifiers

- Plug & play audio interface connects microphones, instruments and line signals with your computer for recording and playback
- Compatible with PC and Mac - no setup required
- High-resolution AD/DA converters (16 bits/ 44.1 kHz and 48 kHz) for high-end audio quality
- High-speed USB 2.0 support
- 2 microphone/hi-Z instrument inputs (combination XLR/6.3 mm jack, bal.), switchable
- +48 V phantom power can be switched on, status LED
- Line input (stereo RCA)
- Analog inputs with gain control and signal/clip LED
- Digital S/PDIF input and output (RCA)
- Monitoring of input and output via adjustable stereo headphones output (3.5 mm jack (1/8"))
- Adjustable stereo line output (6.3 mm jack, bal.) for PA applications
- Power supply via USB, supplied 9 V power unit or 9 V block battery
- The interface can also be used without a computer e.g. as an independent microphone preamplifier for direct monitoring
- Incl. USB cable
- Works with any customary software for PC and Mac
- Powered by a battery/battery pack

OMNITRONIC VM-220 S PRO Vocal microphone

Universal dynamic microphone

- Versatile dynamic microphone with cardioid characteristic

Logistic

- Ideal for song transmission or instrument controlling
- Well-balanced frequency range for natural sound
- Handles high volumes without distortion
- Effective low frequency proximity effect due to flat top grille
- Low-wear reed switch, silent during operation
- Robust diecast body and solid steel basket, applicable for touring
- Delivery includes XLR/jack cable

Technical specifications:

| | |
|---------|---------|
| Weight: | 1,15 kg |
|---------|---------|

OMNITRONIC ADI-004M Interface

| | |
|----------------------------|---|
| Power consumption: | 6,00 W |
| Battery: | 1 x 9.0 V E block 6F22 zinc carbon included |
| Dimensions: | Width: 14,4 cm Depth: 12,7 cm Height: 5 cm |
| Weight: | 0,65 kg |
| Power supply: | 9 V AC/DC, 150 mA via USB port, power unit or battery |
| Frequency range: | 20-20000 Hz, ± 1 dB |
| THD: | <0.01 % |
| S/N ratio: | 90 dB |
| Input impedance: | 1 kohms (mic), 40 kohms (hi-Z) |
| Maximum gain: | 48 dB |
| Inputs: | 2 x hi-Z/mic (combination XLR/6.3 mm jack, bal.), 1 x line (stereo RCA), S/PDIF (RCA) |
| Outputs: | 1 x line L/R (6.3 mm jack, bal.), headphones (3.5 mm stereo jack), S/PDIF (RCA), USB (type B) |
| AD/DA converter: | 16 bits |
| Sampler frequency: | 44.1 kHz or 48 kHz |
| Required operating system: | Windows 98SE/ME/2000/XP/Vista, Mac OS 9.1/OS X |

OMNITRONIC VM-220 S PRO Vocal microphone

| | |
|----------------------|-----------------|
| Capsule type: | Dynamic |
| Frequency range: | 100 - 14000 Hz |
| Weight: | 0,5 kg |
| Type: | Dynamic |
| Directivity pattern: | Cardioid |
| Impedance: | 600 ohms |
| Sensitivity: | -73 dB |
| Connector: | 3-pin XLR, bal. |

Cable: 3-pin XLR, bal./6.3 mm jack, unbal.
