



The article is no longer in our assortment.

Features:

EUROLITE PAR-56 Lite Spot

PAR-56 spot in steel sheet housing

- Ideal for small discotheques or compact lighting-systems for bands
- Delivery includes silicone-cable and color filter frame
- Fourth snap-clamp for the color-filter-frame
- Protection grille on the rear housing cover - complies with CE-regulations
- For permanent installations or road-use
- For PAR-56 lamps
- Different radiation angles possible (spot, medium or flood)
- For PAR 56

OMNILUX PAR-56 230V/300W NSP 2000h H

Special lamp for show effect lighting

- Dimmable
- Very high color rendering index (CRI)

Logistic

Technical specifications:

Weight: 14,27 kg

Legal specifications

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE PAR-56 Lite Spot

Power supply:	230 V AC, 50 Hz
Power consumption:	310 W
IP classification:	IP20
Housing color:	Black
Dimensions:	Width: 21,5 cm Depth: 23,5 cm Height: 24 cm
Weight:	1,25 kg
Dimensions (L x W x H):	240 x 215 x 235 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNILUX PAR-56 230V/300W NSP 2000h H

Operating voltage:	230
Nominal wattage:	300 W
Base:	GX16d
Lamp type:	Incandescent lamp; halogen lamp; reflector lamp
Lamp specification:	Dimmable
Beam angle:	10°
Color of light:	White
Color temperature:	2800K
Color rendering index (CRI):	99,3 Ra
Lead time:	0,5 s
Construction:	PAR-56
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	2000 h
Luminous flux:	3500 lm
Wavelength:	778 nm
Dimensions (LxD):	127x178 mm
Weight:	0,56 kg
EPREL-Nr:	1273391