



Features:

EUROLITE PAR-56 Spot Long with Cable bk

Long PAR-56 housing (with open cable ends)

- Rugged metal housing
- Blackened tube for precise light output
- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Strong extension spring for safe hold and for quick opening of the rear housing cover
- Strong cable tension relief
- With mounting bracket
- For PAR 56

OMNILUX PAR-56 230V/300W NSP 2000h H

Special lamp for show effect lighting

- Dimmable
- Very high color rendering index (CRI)

Technical specifications:

Logistic

Weight:	1.86 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE PAR-56 Spot Long with Cable bk

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 500 W
Protection class:	Protection class I
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0.7 m
Base:	GX16d
Lamp type:	Selectable
Color generation:	Via color filter frame
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 36 cm Width: 23 cm Height: 23.5 cm
Weight:	1.30 kg
Dimensions:	Length: 22.5 cm Width: 22.5 cm Diameter: Ø 17.6 cm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNILUX PAR-56 230V/300W NSP 2000h H

Operating voltage:	230
Nominal wattage:	300 W
Base:	GX16d
Lamp type:	Incandescent lamp; halogen lamp; reflector lamp
Lamp specification:	Dimmable
Beam angle:	10°
Color of light:	White
Color temperature:	2800K
Color rendering index (CRI):	99.3 Ra
Lead time:	0.5 s
Construction:	PAR-56
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	2000 h
Luminous flux:	3500 lm
Wavelength:	778 nm

Dimensions (LxD):	127x178 mm
Weight:	0.56 kg
EPREL-Nr:	1273391

Scope of delivery:

- 1 x spotlight
- 1 x filter frame
- 1 x lamp clamping ring
- 1 x user manual