



**The article is no longer in our assortment.**

### Features:

#### EUROLITE Raylight PAR-64,GY-9.5 Socket long

The alternative to traditional lamps

- Immediately and without changing the wiring, exchangeable by flanged on pin socket (GX 16) against a PAR-64 lamp
- Cost savings, as only the burner must be replaced at a lamp change
- Longlife lamp types (up to 2.000 h) also save time and money
- Low weight

#### EUROLITE PAR-64 Spot Long with Cable sil

Long PAR-64 housing (with open cable ends)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Strong cable tension relief
- With mounting bracket
- Available in various colors
- For PAR 64
- For application areas such as: Advertisement/Shop window; decoration; clubs/dancing school

#### Package contents

- 1 x spotlight, 1 x filter frame, 1 x lamp clamping ring, 1 x user manual

### Logistic

## OMNILUX A1 230V/500W GY-9.5 75h

Special lamp for show effect lighting

- One-sided base
- Easy lamp replacement
- Dimmable
- Very high color rendering index (CRI)

### Technical specifications:

---

|                      |  |
|----------------------|--|
| Weight:              | 1,81 kg                                      |
| Legal specifications |  |
| Special product:     | Not designed for household room illumination |
| Intended use:        | Show effect lighting                         |

## EUROLITE Raylight PAR-64,GY-9.5 Socket long

|                        |                     |
|------------------------|---------------------|
| Power supply:          | 230 V AC, 50 Hz     |
| Power consumption:     | 500 W               |
| Base:                  | GY9.5; GX16d        |
| Beam angle (1/2 peak): | NSP                 |
| Color:                 | Alu colored         |
| Dimensions:            | Diameter: Ø 20,3 cm |
| Weight:                | 0,14 kg             |

## EUROLITE PAR-64 Spot Long with Cable sil

|                       |  |
|-----------------------|--|
| Power supply:         | 230 V AC, 50 Hz                                      |
| Power consumption:    | Max. 1000 W  |
| IP classification:    | IP20   |
| Protection class:     | Protection class I                                   |
| Power connection:     | Fixed supply cord with open wires                    |
| Cable length:         | Approx. 0,7 m  |
| Base:                 | GX16d  |
| Lamp type:            | Selectable   |
| Color generation:     | Via color filter frame (optional)                    |
| Housing color:        | Silver   |
| Attachment system:    | Mounting bracket                                     |
| Slot for spot length: | 25,7 cm x 25,7 cm                                    |
| Dimensions:           | Length: 41,5 cm<br>Width: 26,5 cm<br>Height: 34,5 cm |
| Weight:               | 1,63 kg  |
| Filter frame          |  |

|             |                     |
|-------------|---------------------|
| Dimensions: | Length: 25,5 cm     |
|             | Width: 25,5 cm      |
|             | Diameter: Ø 20,2 cm |

---

Legal specifications

---

|                  |  |
|------------------|--|
| Special product: | Not designed for household room illumination |
| Intended use:    | Show effect lighting                         |

---

**OMNILUX A1 230V/500W GY-9.5 75h**

|                                  |                  |
|----------------------------------|------------------|
| Voltage (lamps):                 | 230 V, AC        |
| Nominal wattage:                 | 500 W            |
| Base:                            | GY9.5            |
| Lamp type:                       | Halogen lamp     |
| Lamp specification:              | Dimmable         |
| Beam angle:                      | 310°             |
| Color of light:                  | White            |
| Color temperature:               | 2700K            |
| Color rendering index (CRI):     | 100 Ra           |
| Lead time:                       | 0,2 s            |
| Construction:                    | Bi pin           |
| Operating temperature max.:      | 40° C            |
| Operating temperature min.:      | 20° C            |
| Burning position:                | S180 (universal) |
| Lamp life:                       | 75 h             |
| Luminous flux:                   | 7200 lm          |
| Wavelength:                      | 778 nm           |
| Lamp current:                    | 2,17 A           |
| Dimensions (LxD):                | 78x18 mm         |
| Weight:                          | 0,02 kg          |
| Energy efficiency class (A - G): | G                |
| EPREL-Nr:                        | 1519666          |

---