



Features:

OSRAM HSD 250/60 4ArXS GY-9.5 2000h

HMI / MSR / HMP / OMI lamps

- Extremely high light output
- Best color rendering
- Light output three to four times higher in comparison to filament light
- Light is generated via an arc between two electrodes
- Spectrum similar to daylight (between 4500 and 6500 K)
- Constant color temperature and color rendering behaviour over the whole lamp life
- Photographic industry
- Halogen metal evaporation lamps provide a spectrum composed of a lot of lines, in contrast to temperature radiators, as halogen-incandescent lamps
- Good color rendering index (CRI)
- For further information about this product, please refer to the Data Sheet under "Downloads"

OMNILUX OSD 90V/250W GY-9.5 1500h 6700K

- For further information about this product, please refer to the Data Sheet under "Downloads"

OSRAM HMI 575/GS 95V/575W SFc-10 1000h

HMI / MSR / HMP / OMI lamps

- Extremely high light output
- Best color rendering
- Light output three to four times higher in comparison to filament light

Logistic

- Light is generated via an arc between two electrodes
- Spectrum similar to daylight
- Constant color temperature and color rendering behaviour over the whole lamp life
- Halogen metal evaporation lamps provide a spectrum composed of a lot of lines, in contrast to temperature radiators, as halogen-incandescent lamps
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

OMNILUX OMI 575 95V/575W SFC-10 500h

HMI / MSR / HMP / OMI lamps

- Extremely high light output
- Best color rendering
- Light output three to four times higher in comparison to filament light
- Light is generated via an arc between two electrodes
- Spectrum similar to daylight
- Constant color temperature and color rendering behaviour over the whole lamp life
- Halogen metal evaporation lamps provide a spectrum composed of a lot of lines, in contrast to temperature radiators, as halogen-incandescent lamps
- Hot restrike
- Very high color rendering index (CRI)
- For further information about this product, please refer to the Data Sheet under "Downloads"

OSRAM HMI 1200W/DXS 100V/1200W SFC-15.5

HMI / MSR / HMP / OMI lamps

- Extremely high light output
- Best color rendering
- Light output three to four times higher in comparison to filament light
- Light is generated via an arc between two electrodes
- Spectrum similar to daylight
- Constant color temperature and color rendering behaviour over the whole lamp life
- Halogen metal evaporation lamps provide a spectrum composed of a lot of lines, in contrast to temperature radiators, as halogen-incandescent lamps
- Hot restrike
- Very high color rendering index (CRI)
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

OMNILUX OBA 1200 100V/1200W SFC-15 5600K

HMI / MSR / HMP / OMI lamps

- Extremely high light output
- Best color rendering
- Light output three to four times higher in comparison to filament light
- Light is generated via an arc between two electrodes
- Constant color temperature and color rendering behaviour over the whole lamp life
- Halogen metal evaporation lamps provide a spectrum composed of a lot of lines, in contrast to temperature radiators, as halogen-incandescent lamps
- Hot restrike
- Good color rendering index (CRI)
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 1.20 kg

Special product: Not designed for household room illumination

Intended use: Show effect lighting

OSRAM HSD 250/60 4ArXS GY-9.5 2000h

Voltage (lamps): 90 V

Nominal wattage: 250 W

Base: GY9.5

Lamp type: Discharge lamp

Color temperature: 6000K

Color rendering index (CRI): 85 Ra

Burning position: S180 (universal)

Lamp life: 2000 h

Luminous flux: 17000 lm

Lamp current: 3.1 A

Dimensions (LxD): 108x23 mm

Special product: Not designed for household room illumination

Intended use: Show effect lighting

OMNILUX OSD 90V/250W GY-9.5 1500h 6700K

Voltage (lamps): 90 V

Nominal wattage: 250 W

Base: GY9.5

Lamp type: Discharge lamp

Color temperature: 6700K

Burning position: S180 (universal)

Lamp life: 1500 h

Luminous flux: 16000 lm

Lamp current: 3.5 A

Dimensions (LxD): 108x22.5 mm

Weight: 0.03 kg

EPREL-Nr: 2033780

Special product: Not designed for household room illumination

Intended use: Show effect lighting

OSRAM HMI 575/GS 95V/575W SFc-10 1000h

Operating voltage: 95

Nominal wattage: 575 W

Base: SFc10

Lamp type: Discharge lamp

Lamp specification: Dimmable
Hot restrike

Color temperature: 6000K

Color rendering index (CRI):	90 Ra
Construction:	Double-sided socket
Burning position:	S180 (universal)
Lamp life:	1000 h
Luminous flux:	49000 lm
Lamp current:	7 A
Dimensions (LxD):	136x21 mm
Weight:	0.04 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNILUX OMI 575 95V/575W SFc-10 500h

Operating voltage:	95
Nominal wattage:	575 W
Base:	SFc10
Lamp type:	Discharge lamp
Lamp specification:	Hot restrike
Color temperature:	6500K
Color rendering index (CRI):	90 Ra
Construction:	Double-sided socket
Burning position:	S180 (universal)
Lamp life:	500 h
Luminous flux:	49000 lm
Lamp current:	7 A
Dimensions (LxD):	136x21 mm
Weight:	0.04 kg
Energy efficiency class (A - G):	G
EPREL-Nr:	1507637

OSRAM HMI 1200W/DXS 100V/1200W SFc-15.5

Operating voltage:	100
Nominal wattage:	1200 W
Base:	SFc15
Lamp type:	Discharge lamp
Lamp specification:	Hot restrike
Color temperature:	6000K
Color rendering index (CRI):	90 Ra
Burning position:	S180 (universal)
Lamp life:	1000 h
Luminous flux:	110000 lm
Lamp current:	13.8 A
Dimensions (LxD):	220x27 mm

Weight:	0.11 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNILUX OBA 1200 100V/1200W SFc-15 5600K

Operating voltage:	100
Nominal wattage:	1200 W
Base:	SFc15
Lamp type:	Discharge lamp; discharge lamp
Lamp specification:	Hot restrike
Color temperature:	5600K
Color rendering index (CRI):	80 Ra
Construction:	Double-sided socket
Burning position:	S180 (universal)
Lamp life:	750 h
Luminous flux:	110000 lm
Lamp current:	13.8 A
Dimensions (LxD):	220x28 mm
Weight:	0.12 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery: