



The article is no longer in our assortment.

Features:

EUROLITE PAR-56 Spot Short with Cable sil

PAR-56 housing with silicone cable and open cable ends

- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong cable tension relief
- The device is cooled by passive convection cooling
- With mounting bracket
- For PAR 56

Package contents

- 1 x spotlight, 1 x filter frame, 1 x lamp clamping ring, 1 x user manual

Logistic

OMNILUX PAR-56 230V/300W NSP 2000h H

Special lamp for show effect lighting

- Dimmable
- Very high color rendering index (CRI)

Technical specifications:

Weight:

1,36 kg

Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE PAR-56 Spot Short with Cable sil

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 500 W
IP classification:	IP20
Protection class:	Protection class I
Suitable lamp:	Max. 230 V/500 W PAR-56
Power connection:	Fixed supply cord with open wires
Cable construction:	3 x 0,75 mm² H05SS-F
Cable length:	Approx. 0,8 m
Base:	GX16d
Lamp type:	Selectable
Color generation:	Via color filter frame
Cooling:	Passive convection cooling
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	21,4 cm x 21,8 cm
Dimensions:	Length: 26 cm Width: 23,5 cm Height: 22 cm
Weight:	0,80 kg
Mounting bracket	
Diameter mounting holes:	2 x Ø13mm
Material:	Metal, 2 mm
Filter frame	
Diameter mounting holes:	4 x Ø8mm
Shape:	Octagonal
Grid size:	10 x 10 mm
Material:	Aluminum, 0,6 mm
Dimensions:	Length: 21,5 cm Width: 21,5 cm Diameter: Ø 17,1 cm
Lamp clamping ring	
Material:	Steel, 4 mm
Color:	Silver
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNILUX PAR-56 230V/300W NSP 2000h H

Operating voltage:	230
Nominal wattage:	300 W
Base:	GX16d
Lamp type:	Incandescent lamp; halogen lamp; reflector lamp
Lamp specification:	Dimmable
Beam angle:	10°
Color of light:	White
Color temperature:	2800K
Color rendering index (CRI):	99,3 Ra
Lead time:	0,5 s
Construction:	PAR-56
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	2000 h
Luminous flux:	3500 lm
Wavelength:	778 nm
Dimensions (LxD):	127x178 mm
Weight:	0,56 kg
EPREL-Nr:	1273391