

ALUTRUSS TRILOCK Karree 3,5m Λ

Art. No.: 09009942

GTIN:





The article is no longer in our assortment.

Features: Logistic

ALUTRUSS TRILOCK 6082AL-31 3-Way Corner ∧ right

3-point truss system

- Low weight
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; Clubs/dancing school

Package contents

- 2 x connection Set

ALUTRUSS TRILOCK 6082AL-32 3-Say Corner Λ left

3-point truss system

- Low weight
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; Clubs/dancing school

Package contents

- 2 x connection Set

ALUTRUSS TRILOCK Base Plate QTG-male

- Trusspipe: 50 mm

- Made in Europe

ALUTRUSS TRILOCK 6082-2500 3-Way Cross Beam

3-point truss system

- Low weight
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; Clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x connection Set

Technical specifications:

Weight: 106,74 kg

ALUTRUSS TRILOCK 6082AL-31 3-Way Corner ∧ right

Setup:	Easy installation	
Trusspipe:	50 mm x 2 mm	
Color:	Alu colored	
Strut diameter x thickness:	16 x 2mm	
Dimensions:	Length: 50 cm	
	Width: 50 cm	
	Height: 50 cm	
Weight:	6,1 kg	

ALUTRUSS TRILOCK 6082AL-32 3-Say Corner ∧ left

Setup:	Easy installation
Trusspipe:	50 mm x 2 mm
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 50 cm
	Width: 50 cm
	Height: 50 cm
Weight:	6,20 kg

ALUTRUSS TRILOCK Base Plate QTG-male

Trusspipe:	50 mm	50 mm	
Color:	Alu colored		
Weight:	940 g		

ALUTRUSS TRILOCK 6082-2500 3-Way Cross Beam

Setup:	Easy installation	
Trusspipe:	50 mm x 2 mm	
Welding technique:	TIG-welding	
Welding material:	AIMg 5	
Color:	Alu colored	
Strut diameter x thickness:	16 x 2mm	
Dimensions:	Length: 2,5 m	
	Width: 29 cm	
	Height: 25,70 cm	
Weight:	9,80 kg	