



The article is no longer in our assortment.

Features:

ALUTRUSS QUADLOCK 6082L-30 3-way Corner 90°

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school

Package contents

- 2 x connection set

Logistic

ALUTRUSS QUADLOCK End Plate QQGP-Male

- Trusspipe: 50 mm
- Made in Europe
- **cone**
- M8 thread

ALUTRUSS QUADLOCK 6082-2500 4-way Cross Beam

4-point truss system

- Strong EN-AW 6082 alloy for high loads

- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x connection set

Technical specifications:

Weight:	132,40 kg
---------	-----------

ALUTRUSS QUADLOCK 6082L-30 3-way Corner 90°

Setup:	Easy installation
--------	-------------------

Trusspipe:	50 mm x 2 mm
------------	--------------

Color:	Alu colored
--------	-------------

Strut diameter x thickness:	16 x 2mm
-----------------------------	----------

Dimensions:	Length: 50 cm
	Width: 50 cm
	Height: 50 cm

Weight:	7,95 kg
---------	---------

ALUTRUSS QUADLOCK End Plate QQGP-Male

Trusspipe:	50 mm
------------	-------

Color:	Alu colored
--------	-------------

Weight:	1,45 kg
---------	---------

Cone	
------	--

Thread:	M8 thread
---------	-----------

ALUTRUSS QUADLOCK 6082-2500 4-way Cross Beam

Setup:	Easy installation
--------	-------------------

Trusspipe:	50 mm x 2 mm
------------	--------------

Welding technique:	TIG-welding
--------------------	-------------

Welding material:	AlMg 5
-------------------	--------

Alloy:	AlMgSi1 T6
--------	------------

Color:	Alu colored
--------	-------------

Strut diameter x thickness:	16 x 2mm
-----------------------------	----------

Dimensions:	Length: 250 cm
	Width: 29 cm
	Height: 29 cm

Weight:	11,85 kg
---------	----------