EUROLITE Set EUROLITE LED Bar 252 20° + Softbag

Art. No.: 09009955

GTIN:

The article is no longer in our assortment.

Features:

EUROLITE LED BAR-252 RGB 10mm 20° black

LED bar with 252 LEDs in red, green and blue, 110 cm length and 20°

- DMX512 control via regular DMX controller
- Sound-control via built-in microphone
- Stand-alone mode functions adjustable via DIP switches
- Color change speed and strobe effect adjustable via DIP switches
- Multi-color color changes
- Master/Slave function
- Ideal for bands, stages or solo entertainers
- Perfect in public places, main halls, lounges
- Illuminants: 252 10 mm LEDs (48 x red, 108 x green and 96 x blue)
- Available in 2 LED beam angles: 20° or 40°
- Advantages of LED technology: long life of the LEDs, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- 252 powerful LEDs 10 mm R/G/B
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; Sound to light via Microphone
- Preprogrammed in LED PC-Control 512
- With a beam angle of 20°

EUROLITE SB-12 Soft Bag

Practical black soft bag for LED bars (1 m length), adjustable divider

- Ideal for 1 or 2 LED bars with 1 meter length

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Made of easy-care nylon
- With divider
- With 2 Device compartments
- High-quality workmanship with textile , black
- Interior with foam padding
- 2 carrying straps
- 1 shoulder strap

Technical specifications:

Weight:	4,97 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED BAR-252 RGB 10mm 20° black

Power supply:	230 V AC, 50 Hz
Power consumption:	50,00 W
IP classification:	IP20
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED:	252 x 10 mm R/G/B
DMX channels:	12
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; Sound to light via Microphone
Preprogrammed in:	LED PC-Control 512
Beam angle:	20°
Beam angle (1/2 peak):	20°
Housing color:	Black
Dimensions:	Length: 1,07 m Depth: 6,5 cm Height: 9 cm
Weight:	2,20 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-12 Soft Bag

Maximum load:	20 kg
Carrying strap:	2 pc/pcs
Transport aid:	1 x shoulder strap

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Material:	Textile
Color:	Black
Dimensions:	Width: 1,07 m Depth: 17 cm Height: 18 cm
Weight:	570 g

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.