



### Features:

#### FUTURELIGHT PLB-130 Moving Head

High performance beam with Osram Sirius HRI 132 W lamp

- Parallel beam
- Effect wheel with rotating 8-facet prism
- The prism rotate in both directions and at different speeds
- Motorized focus
- Strobe effect with adjustable speed
- Random strobe effect
- Electronic dimmer (0-100%)
- Exact positioning via 16-bit PAN/TILT movement resolution
- Automatic position correction
- Control panel with LC display for easy configuration
- PAN angle switchable between 630° and 540°
- Stand-alone, master/slave and DMX mode
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- Software upload by optional accessories via DMX link
- With Osram Sirius HRI 132 W lamp
- Gobos
- Gobo effect
- Color wheel with 14 dichroic filters plus open<BR>rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 17 gobos and open<BR>shake effect
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; stand-alone; sound to light via microphone

### Logistic

- With a beam angle of 2°

### ROADINGER Flightcase 4x PLB-130/DMH-80/TMH XB-130

Trunk case with castors

- With 4 device compartments
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Technical specifications:

Weight:	69.40 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### FUTURELIGHT PLB-130 Moving Head

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	190 W
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Fuse:	T 3.15 A fuse replaceable
Lamp type:	Discharge lamp
Max. TILT movement:	265° positioning
Max. PAN movement:	630° positioning
Flash rate:	1 - 20 Hz
Equipment:	Gobos
Color generation:	Color wheel with 14 dichroic filters plus open Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 17 gobos and open Shake effect
DMX channels:	10; 12; 13; 16
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX; stand-alone; sound to light via microphone

Fixtures available for:	LED PC-Control 512; Light Captain; Light J
Beam angle (1/2 peak):	2°
Housing color:	Black
Dimensions:	Width: 25 cm Depth: 30 cm Height: 40 cm
Weight:	11.70 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Energy efficiency class (A++ - E):	G

#### **ROADINGER Flightcase 4x PLB-130/DMH-80/TMH XB-130**

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Accessory compartment:	10 cm x 45 cm x 38.5 cm
Inside dimensions:	77 cm x 45 cm x 40.5 cm
Device compartment:	31.5 cm x 21.5 cm x 38.5 cm
Dimensions:	Width: 81 cm Depth: 50 cm Height: 43 cm
Weight:	22.60 kg

#### **Scope of delivery:**

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 1 x omega bracket
- 1 x XLR cable