

OMNITRONIC EP-220 Preamplifier

Universal 19" preamplifier



The article is no longer in our assortment.

Features:

- For quick-access music playback control in restaurants, gyms and retail locations
- 4 stereo line inputs
- Additional AUX input on the front panel
- Audio source selector
- Controls for volume, bass and treble
- 1 microphone input with controls for volume, bass and treble on the front panel
- 3 stereo master outputs
- Rack installation, 1 U
- (19") 48.3 cm rack installation

Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	5 W
Equalizer:	Master: 1 x 2-band tone control stereo
Housing design:	(19") 48.3 cm rack installation
Dimensions:	Width: 48,3 cm
	Depth: 12,8 cm
	Height: 4,45 cm
Weight:	1,86 kg
Frequency range:	20-20000 Hz, ±0.5 dB

Logistic

EAN / GTIN: 4026397565034 Weight: 2,23 kg Length: 0.55 m Width: 0.19 m Heigth: 0.08 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

S/N ratio:	100 dB
Distortion factor:	0.05 %
Input impedance:	20 kohms (balanced), 10 kohms (unbalanced)
Input sensitivity:	1 V
Input connectors:	
Line 1-4:	RCA L/R
Mic:	combination XLR/6.3 mm jack
Aux:	3.5 stereo jack
Output connectors:	RCA L/R, XLR L/R, 6.3 mm jack L/R
Dimensions:	483 x 128 x 44 mm
	rack installation, 1 U