

OMNITRONIC RS-1222 Recording mixer

User-friendly 12-channel studio and live mixer

Art. No.: 10040100

GTIN: 4026397183252



The article is no longer in our assortment.

Features:

- Low-noise 12-channel mic/line mixer
- 4 mono inputs with XLR sockets, +48V phantom power and balanced line inputs
- Insert or Direct Out for every mono channel
- 4 stereo inputs with balanced 6.3 mm jack sockets
- Stereo inputs can also be operated mono
- 3-band EQ with semi-parametric mids for all mono inputs
- 4-band EQ for all stereo inputs
- Peak LED and switchable Low Cut per mono input
- 2 x aux send (pre/post) per channel for controlling external effectors and for monitoring
- 2 x stereo aux return with balanced 6.3 mm jack sockets
- Separate Main Mix, Control Room and headphones outputs
- Tape inputs and outputs
- Precise 10-fold stereo LED meter
- 60 mm high-quality faders

Logistic

EAN / GTIN: 4026397183252

Weight: 6,20 kg

Length: 0.49 m

Width: 0.44 m

Height: 0.12 m

Technical specifications:

| | |
|--------------------|------------------------------------------------|
| Power consumption: | 25,00 W |
| Dimensions: | Width: 37 cm Depth: 40 cm Height: 5,5 cm |
| Weight: | 5,30 kg |
| Power supply: | 2 x 20 V AC, 50/60 Hz |

| | |
|------------------------------|-------------------------------|
| | via included power unit |
| Inputs: | |
| 4 mono | XLR or balanced 6.3 mm jack |
| 4 Inserts | 6.3 mm jacks |
| 4 stereo | balanced 6.3 mm jacks |
| 2 Aux Return: | balanced 6.3 mm jacks |
| 1 Tape In | RCA |
| Outputs: | |
| 2 Main Out: | XLR and balanced 6.3 mm jacks |
| 1 Control Room | balanced 6.3 mm jacks |
| 2 Aux Send: | balanced 6.3 mm jacks |
| 4 Direct Out | 6.3 mm jacks |
| 1 Tape Out | RCA |
| Headphones | unbalanced 6.3 mm jack |
| Frequency range: | |
| Microphone: | 10-60000 Hz, ± 3 dB |
| Mono: | 10-60000 Hz, ± 3 dB |
| Stereo: | 10-55000 Hz, ± 3 dB |
| Distortion: | 0.01 % |
| S/N ratio: | 112 dB |
| Tone control/mono channel: | |
| High: | ± 15 dB at 12 kHz |
| Mid: | ± 15 dB at 250 Hz - 6 kHz |
| Low: | ± 15 dB at 80 Hz |
| Tone control/stereo channel: | |
| High: | ± 15 dB at 12 kHz |
| Hi Mid: | ± 15 dB at 3 kHz |
| Lo Mid: | ± 15 dB at 500 Hz |
| Low: | ± 15 dB at 80 Hz |
| Dimensions (W x D x H): | 370 x 400 x 55 mm |