

OMNITRONIC LRS-1424FX USB Live Recording Mixer

Live recording mixer with 14 inputs, USB audio interface and DSP FX unit

Art. No.: 10040232

GTIN: 4026397466911



The article is no longer in our assortment.

Features:

- Built-in USB audio interface allows recordings and playback of digital audio files with a computer (PC and Mac)
- 24 bit DSP FX unit with 100 different effects, e.g. reverb, chorus, flanger, delay, pitch shifter and multi-effects
- 4 mono input channels with gain control, 3-way EQ, low cut and pan control
- 2 stereo input channels with 3-way EQ and balance control
- All channels with clip LED, mute, main mix and subgroup routing switches, solo and PFL functions
- Adjustable stereo aux return inputs and FX send outputs
- Inserts for the mono input channels
- Tape input and output
- Separate main mix and control room outputs
- 2 subgroups with separate output
- Adjustable headphones output
- All channels with 60 mm fader
- +48 V phantom power, can be switched centrally
- Precise 8-digit stereo LED level display
- BNC connector for Flexilight gooseneck lights

Logistic

EAN / GTIN: 4026397466911

Weight: 4,25 kg

Length: 0.40 m

Width: 0.33 m

Height: 0.20 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 40,00 W

Frequency range: 20 - 20000 Hz

| | |
|-------------------------|---|
| Dimensions: | Width: 29 cm Depth: 11,5 cm Height: 35,5 cm |
| Weight: | 3,55 kg |
| Inputs/sensitivity: | |
| Mic, mono | 0.9 mV, XLR bal. |
| Line In, mono | 0.9 mV, 6.3 mm jack bal. |
| Insert | 100 mV, 6.3 mm jack unbal. |
| Stereo Aux Return: | 60 mV, 6.3 mm jack L/R bal. |
| Line In, stereo | 60 mV, 6.3 mm jack L/R bal. |
| Tape In | 400 mV, RCA L/R |
| Outputs/level: | |
| Main Out: | 1.5 V, XLR and 6.3 mm jack L/R bal. |
| ALT 3-4 Out | 750 mV, 6.3 mm jack bal. |
| Control Room | max. 10 V, 6.3 mm jack L/R unbal. |
| Aux Send: | max. 10 V, 6.3 mm jack unbal. |
| Tape Out | 750 mV, RCA L/R |
| Headphones | 6.3 mm jack unbal. |
| Headphones impedance: | >8 ohms |
| USB port: | 1.1, type B |
| Distortion: | 0.05 % |
| S/N ratio: | 89 dB |
| Tone control/channel: | |
| Treble: | ±15 dB at 12 kHz |
| Middle: | ±15 dB at 2.5 kHz |
| Bass: | ±15 dB at 80 Hz |
| Low Cut: | 75 Hz, 18 dB/octave |
| Dimensions (W x D x H): | 355 x 290 x 115 mm |