

OMNITRONIC MRS-1002USB Recording Mixer

Compact audio mixer with 10 inputs and USB interface

Art. No.: 10040271

GTIN: 4026397513882



The article is no longer in our assortment.

Features:

- Built-in USB audio interface allows recordings and playback of digital audio files with a computer (PC and Mac)
- Full duplex USB port allows simultaneous recording and playback
- 2 mono input channels with gain control, 3-way EQ and pan control
- 4 stereo input channels with 3-way EQ and balance control
- Tape input and output
- Separate main mix and control room outputs
- Adjustable headphones output
- +48 V phantom power, can be switched centrally
- Precise 4-digit stereo LED level meter
- Rugged, compact metal housing
- Desktop console housing

Package contents

- 1 x user manual, 1 x external mains adapter, 1 x mixer, 1 x USB cable

Logistic

EAN / GTIN: 4026397513882

Weight: 2,23 kg

Length: 0.35 m

Width: 0.29 m

Height: 0.08 m

Technical specifications:

Power supply: 230 V AC, 50 Hz
17V

Power consumption: 27,00 W

Protection class: Protection class III

Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Frequency range:	20 - 20000 Hz
S/N ratio:	>74 dB
THD:	<0,05 % at 1 kHz
Control elements:	Phantom power switch
Status LED:	Power, clip, master level meter, phantom power
Connections:	Input: microphone via 2 x 3-pin XLR Input: microphone via 2 x 3.5 mm jack (mono) mounting version Input: line via 4 x 6.3 mm jack socket (mono) mounting version Input: stereo via 1 x stereo RCA Input: line via 1 x USB B (F) mounting version Input: AUX returns via 2 x 6.3 mm jack socket (mono) mounting version Output: master via 2 x 6.3 mm jack socket (mono) mounting version Output: control room via 2 x 6.3 mm jack socket (mono) mounting version Output: AUX sends via 1 x 6.3 mm jack socket (stereo) mounting version Output: headphones via 1 x 6.3 mm jack socket (stereo) mounting version Output: line via 1 x stereo RCA
Channels:	Input channel: 2 x mono via XLR or jack, channel control via rotary dial, 3-band tone control EQ 80Hz/2,5kHz/12kHz, 1 Send/AUX, gain control, panoramacontrol Input channel: 2 x stereo via jack, channel control via rotary dial, 3-band tone control EQ 80Hz/2,5kHz/12kHz, 1 Send/AUX, balancecontrol Input channel: 1 x stereo via RCA, routing master bus switch Master output: 1 x stereo via jack, channel control via rotary dial Headphones output: 1 x stereo via jack, channel control via rotary dial
USB port:	USB 2.0, type B
Housing design:	Desktop console housing
Dimensions:	Width: 18,9 cm Depth: 26 cm Height: 7,2 cm
Weight:	2,02 kg