

OMNITRONIC LMC-3242FX USB Mixing Console

PRO audio mixer with British-style EQ, compressor, effect unit and USB interface

Art. No.: 10040287

GTIN: 4026397654837



List price: 570.01 €

incl. 19% VAT.

Description:

Professional live mixing consoles with British EQ, FX unit and USB interface
Effortlessly achieve the right sound with the LMC series by OMNITRONIC! The incredibly user-friendly mixing consoles provide a warm, natural sound with outstanding audio parameters, an extensive set of features and maximum reliability - ideal for professional studio recordings, live performances, and fixed PA installations. Especially the 2022FX has several useful features that are unparalleled in this price range: feedback detection system, voice canceller, and 3D stereo surround effect.

All mono channels feature extremely low-noise, top-notch microphone preamps that offer an extraordinary 130 dB of dynamic range, and a bandwidth ranging from below 10 Hz to over 200 kHz for crystal-clear signal reproduction. The incredibly warm and natural equalizers used for all channel strips are based on classic "British EQ" circuitry from mixing consoles of the '60s and '70s.

Additionally, your LMC series mixing console has a studio-grade compressor with easy one-knob functionality on each mono channel plus a 24-bit FX processor with 16 editable effects which can be added to individual channels, busses or the main mix. Utilizing the built-in USB audio interface with up to 48 kHz sample rate, you can link your Windows or Mac computer and record your sessions instantly.

Features:

- 14 mono input channels with gain control, 3-way EQ with semi-parametric mid band, low cut and pan control
- 14 inserts for flexible connection of outboard equipment on each mono channel
- 4 stereo input channels with gain control, 4-way EQ, low cut (ch. 15-18) and balance control
- State-of-the-art, low-noise mic preamps with 130 dB dynamic range and high headroom

Logistic

EAN / GTIN: 4026397654837

Weight: 10,70 kg

Length: 0.65 m

Width: 0.53 m

Height: 0.21 m

- Exceptional British EQs for warm and musical sound
- Studio-grade compressors with easy one-knob functionality and control LED on each mono channel
- 24-bit DSP FX unit with 16 editable presets, tap function and storable user parameter settings
- Built-in USB audio interface allows recordings and playback of digital audio files with a computer (PC and Mac)
- Intelligent feedback detection system makes eliminating feedback frequencies easy
- 4 aux sends per channel: 2 pre/post-fader switchable for flexible routing
- 4 subgroups with separate faders and outputs for added routing flexibility
- 4 stereo aux returns with flexible routing
- 14 direct outputs for recordings
- Clip LEDs on all channels
- Routing switches for mute, main mix, subgroup and solo/PFL on all channels
- 2 separate main mix outputs with inserts
- 2 phones and control room outputs with multi-input source matrix
- CD/tape input assignable to main mix or control room/phones outputs, CD/tape output
- Precise 12-digit level meter
- BNC lamp socket
- FX mute with remote control via footswitch
- +48 V phantom power, can be switched centrally
- Incl. brackets for rack installation
- Digital signal processor 24 bit with 16 effects
- The device can be connected via USB to the PC
- (19") 48.3 cm rack installation

Technical specifications:

| | |
|----------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 50 W |
| Power connection: | Mains input IEC connector (M) mounting version Power supply cord with safety plug (provided) |
| Frequency range: | 20 - 20000 Hz |
| S/N ratio: | >110 dB |
| THD: | <0,05 % at 1 kHz |
| DSP: | Digital signal processor 24 bit with 16 effects |
| Phantom power: | 48 V DC |
| Crossover frequency: | High-pass 75 Hz, 18db/oct |
| Impedance: | Input Microphone: 2,6 kOhm , bal. Input line: 10 kOhm , bal. Input 2-Track: 10 kOhm Input AUX returns: 10 kOhm , bal. Insert 10 kOhm , unbal. |
| Gain: | Input: variable |
| Crosstalk: | >89 dB |
| Display type: | Monochrome 2 digits 7-segment LED display |
| Control elements: | Encoder, power switch, phantom power switch |
| Status LED: | Master level meter, clip, Gain reduction, Mute, phantom power; power |
| Connections: | 1 x lamp via BNC (F) Input: 16 x Microphone via 3-pin XLR Input: 22 x line via 6.3 mm jack socket (mono) mounting version Input: 1 x 2-Track via stereo RCA Output: 2 x headphones via 6.3 mm jack socket (stereo) mounting version Output: 1 x rec. via stereo RCA |

Output: 2 x master via 3-pin XLR
 Output: 2 x master via 6.3 mm jack socket (mono) mounting version
 Output: 8 x sub groups via 6.3 mm jack socket (mono) mounting version
 Output: 14 x Direct out via 6.3 mm jack socket (mono) mounting version
 Output: 4 x AUX sends via 6.3 mm jack socket (mono) mounting version
 Output: 1 x Foot control via 6.3 mm jack socket (stereo) mounting version
 Output: 2 x control room via 6.3 mm jack socket (mono) mounting version
 Output: 8 x AUX returns via 6,3-mm-jack (bal.)
 Insert: 14 x Chanal via 6.3 mm jack socket (stereo) mounting version
 Insert: 2 x master via 6.3 mm jack socket (stereo) mounting version

Chanals:

Input chanel: 14 x mono via XLR or jack, channel control via 60mm fader, 3-band EQ-Poti with semiparametric mid-band EQ ± 15 dB at 80Hz/500Hz/3kHz/12kHz, 4 Send/AUX, pre-post switch, gain control, low cut switch, adjustable single-knob compressor, Routing Sub group bus switch, Routing master bus switch, panoramacontrol, Mute control, solo switch

Input chanel: 2 x stereo via XLR or jack, channel control via 60mm fader, 4-band EQ-poti EQ ± 15 dB at 80Hz/100-8kHz/12kHz, 4 Send/AUX, pre-post switch, gain control, low cut switch, Routing Sub group bus switch, Routing master bus switch, balancecontrol, Mute control, solo switch,

Input chanel: 2 x stereo via Plug 6,3mm/3,5mm (Jack), channel control via 60mm fader, 4-band EQ-poti EQ ± 15 dB at 80Hz/500Hz/3kHz/12kHz, 4 Send/AUX, pre-post switch, gain control, Routing Sub group bus switch, Routing master bus switch, balancecontrol, Mute control, solo switch,

Master output: stereo, channel control via 60mm fader

Max. level:

Output: master +28 dBu, bal.
 Output: sub groups +22 dBu, unbal.
 Output: control room +22 dBu, unbal.
 Output: Direct out +22 dBu, unbal.
 Output: rec. +22 dBu
 Output: headphones +19 dBu, unbal.
 Output: AUX sends +22 dBu, unbal.

USB port:

Typ B

PC connect:

Via USB

Housing design:

(19") 48.3 cm rack installation

Dimensions:

Width: 59,2 cm
 Depth: 45 cm
 Height: 13,7 cm

Weight:

9,30 kg
