

### **OMNITRONIC CFL-2442 Live Mixer**

24-channel live mixer

Art. No.: 10060350

GTIN: 4026397230888



# The article is no longer in our assortment.

#### **Description:**

Something for everybody. The smallest unit of this CFL live mixer series disposes of 12, the biggest unit disposes of 32 mono inputs. Normally, live mixers have faders from 70 - 80 mm. The CFL series has remarkably long faders that easily reach 100 mm. Although it is very low-priced, the series is highly resistent and by offering four subgroups and four Aux-Sends it is really well equipped. In total: powerful but not pricy.

#### Features:

- 24 mono inputs with XLR sockets and balanced line inputs
- +48V phantom power per channel
- 2 stereo inputs via balanced jacks
- 2 stereo effect returns
- Insert for every mono channel
- High pass filter and 3-band EQ with semi-parametric mids for all mono inputs
- 4 groups for levelling complete signal groups (e.g. drums)
- Mutes for every channel
- 4 aux send (2 pre, 2 post) per channel for controlling the effects and for monitoring
- Separate master, group, monitor outputs
- 100 mm faders
- Precise 12-digit LED meter in subgroups and stereo master

## **Technical specifications:**

Power supply:

115/230 V AC, 50/60 Hz

#### Logistic

EAN / GTIN: 4026397230888

Weight: 23,65 kg Length: 1.09 m Width: 0.26 m Heigth: 0.66 m

| Power consumption:      | 70,00 W                        |
|-------------------------|--------------------------------|
| Dimensions:             | Width: 101 cm                  |
|                         | Depth: 53 cm                   |
|                         | Height: 16 cm                  |
| Weight:                 | 20,20 kg                       |
| Inputs:                 |                                |
| 24 mono                 | XLR/6.3 mm jack, balanced      |
| 24 inserts              | 6.3 mm jack, unbalanced        |
| 2 stereo                | 6.3 mm jacks                   |
| 4 Aux Return:           | 6.3 mm stereo jack, balanced   |
| Outputs:                |                                |
| 2 Main Out:             | XLR/6.3 mm jack, balanced      |
| 1 Monitor               | balanced 6.3 mm jack, balanced |
| 4 Group Out             | 6.3 mm jack, balanced          |
| 4 Aux Send:             | 6.3 mm jack, balanced          |
| Rec Out                 | RCA                            |
| Frequency range:        | 10-60000 Hz, ±3 dB             |
| Dimensions (W x D x H): | 1005 x 530 x 160 mm            |