

OMNITRONIC ZD-160 Zone Distributor

Practical distributor with 1 input and 6 outputs

Art. No.: 10304105

GTIN: 4026397257304



Features:

- Extends every mixer with additional outputs
- 1 stereo XLR input
- 6 stereo zone outputs (XLR)
- Each zone with level control and mono switch
- LED display of signal input and mono/stereo mode
- (19") 48.3 cm rack installation 1 U
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

Logistic

EAN / GTIN: 4026397257304

Weight: 2,70 kg

Length: 0.53 m

Width: 0.27 m

Height: 0.09 m

Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	7 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
S/N ratio:	>69 dB
THD:	<0.2 % at 1 kHz
Impedance:	Input: 45.1 kOhm Output: 125 Ohm
Gain:	15 dB
Max. level:	Output: +22 dB

Input: +9 dBV

Color:	Silver
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Width: 48.3 cm Depth: 12.6 cm Height: 4.45 cm
Weight:	2.31 kg

Scope of delivery:

- 1 x device
- 1 x power cord
- 1 x user manual