

## **OMNITRONIC LH-075 Tube mic preamplifier**

1-channel vacuum tube mic preamplifier with integrated limiter

Art. No.: 10355075 GTIN: 4026397194951











# The article is no longer in our assortment.

#### Features:

- 12AX7 vaccum tube adds warm sound to digital recorders and sound cards
- Signal inputs and outputs via balanced XLR connectors and 6.3 mm jacks
- Limiter can be switched on
- +48 V phantom power can be switched on
- Microphone phase can be switched
- Input attenuation can be switched on (+20 dB)
- Precise 5-digit LED meter with Peak LED for output level
- Adjustable gain
- Adjustable output level
- Modern convex housing design
- Full rubber housing corners for safe operation
- Cables can be routed under the housing
- Operation via supplied power unit

### **Technical specifications:**

Power consumption:	15,00 W
Frequency range:	10 - 20000 Hz
Dimensions:	Width: 15 cm
	Depth: 6 cm
	Height: 13 cm
Weight:	1,2 kg

#### Logistic

EAN / GTIN: 4026397194951 Weight: 1,40 kg Length: 0.23 m Width: 0.16 m Heigth: 0.10 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power supply:	9 V AC, 1500 mA
Input impedance:	2 kohms (XLR), 840 kohms, 6.3 mm jack (1/4")
Output impedance:	600 ohms (XLR), 300 ohms, 6.3 mm jack (1/4")
Maximum output level:	28 dBu (XLR), 22 dBu, 6.3 mm jack (1/4")
Maximum input level:	14 dBu (XLR), 22 dBu, 6.3 mm jack (1/4")
Dynamic range:	>100 dB
Phantom power:	+48 V
Input connectors:	XLR and jack mounting sockets
Output connectors:	XLR and jack mounting plugs
THD:	0.1 %