OMNITRONIC GEQ-215 XL Equalizer 2x15-band

2 x Graphic equalizer 15-band

Art. No.: 10355530

GTIN: 4026397233216

The article is no longer in our assortment.

Features:

- 2-channel version, 2 x 15 frequency controls with 2/3 octave steps
- XL (50 mm) sliding frequency controls with center click
- EQ gain switchable ±6 dB to ±15 dB
- Switchable low cut filter
- Separate level control per channel
- Bypass switch allows instant comparison of the original sound with the equalized sound
- 7-fold LED level meter with clip indicator
- Inputs and outputs via 6.3 mm jack sockets (1/4"), XLR sockets and screw terminals
- Groundlift switch
- Rack installation, 2 U

Logistic

EAN / GTIN: 4026397233216
Weight: 4,30 kg
Length: 0.55 m
Width: 0.25 m
Heigth: 0.12 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	10,00 W
Equalizer:	2 x Graphic equalizer 15-band
Dimensions:	Width: 48,3 cm Depth: 17,5 cm Height: 8,9 cm
Weight:	3,80 kg
Input impedance:	10/20 kohms (unb./bal.)

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Output impedance:	300/150 kohms (unb./bal.)
In/Out connectors:	XLR, jack, screw connectors
S/N ratio:	>95 dB
Crosstalk:	>90 dB
Distortion:	<0.01 %
Frequency range:	20-20000 Hz, ±0.5 dB
Output level:	-~ to +6 dB
Control range:	±6 dBu or ±15 dBu
Frequencies:	2 x 25/40/63/100/160/250/400/630 Hz, 1/1.6/2.5/4/6.3/10/16 kHz
Low Cut:	30 Hz, -3 dB
Dimensions (W x D x H):	483 x 175 x 88 mm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.