

OMNITRONIC XO-230 Active Crossover

Active crossover, stereo 2-way and mono 3-way operation

Art. No.: 10355627

GTIN: 4026397522891



List price: 106.98 €

incl. 19% VAT.

Features:

- 2-way or 3-way stereo operation
- Variable 24 dB per octave Linkwitz-Riley filters
- Crossover frequencies continuously adjustable between 45 Hz and 9.6 kHz
- Low frequency summed (subwoofer) output
- Individual output level controls for each frequency range
- Butterworth low-cut filter (12 dB/octave 40 Hz) to protect subwoofers
- x10 range switch on both channels
- Phase reverse switch on all outputs
- LED indicators for all important functions for easy status identification
- Balanced XLR inputs and outputs
- (19") 48.3 cm rack installation 1 U

Logistic

EAN / GTIN: 4026397522891

Weight: 2,33 kg

Length: 0.54 m

Width: 0.24 m

Height: 0.10 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	8 W
Power connection:	Mains input IEC connector (M) mounting version Power supply cord with safety plug (provided)
S/N ratio:	>100 dB
THD:	<0,05 % at 1 kHz
Crossover frequency:	45-9600 Hz, 24db/oct, Linkwitz-Riley
Impedance:	Input 25 kOhm, unbal.

Input 50 kOhm , bal.
Output 100 Ohm , unbal.
Output 200 Ohm , bal.

Gain:	Input: ± 12 dB Output: - ? to + 6 dB
Filter:	Low cut: 40 Hz 12db/oct Butterworth
Phase invert:	Per output, switchable
Crosstalk:	>80 dB
Control elements:	Mode switch (2-way, stereo/3-way, mono)
Connections:	Input: 2 x line via 3-pin XLR Output: 4 x line via 3-pin XLR
Max. level:	Input: +22 dBu Output: +21 dBu
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Width: 48,3 cm Depth: 15,2 cm Height: 4,45 cm
Weight:	1,87 kg
