

OMNITRONIC XO-23S Active crossover

High-quality stereo crossover



0.90.10.90.

The article is no longer in our assortment.

Features:

- 2-way stereo operation / 3-way mono operation
- Additional Subwoofer output
- 24 dB octave slope
- Crossover frequency control on the front panel
- Frequency range of crossover frequency Low/High band 100 Hz to 7 kHz
- Frequency range of crossover frequency Subwoofer 50 Hz to 350 Hz
- Individual output level controls for all bands
- Low cut switch
- Phase invert control
- XLR inputs and outputs
- Illuminated switches for secure operation in dark environments
- Rack installation

Technical specifications:

Power supply:	230 V AC, 50 Hz	
Power consumption:	10,00 W	
Dimensions:	Width: 48,3 cm	
	Depth: 14,7 cm	
	Height: 4,45 cm	
Weight:	2,15 kg	
Slope:	24 dB / octave	

Logistic

EAN / GTIN: 4026397393101 Weight: 2,50 kg Length: 0.54 m Width: 0.20 m Heigth: 0.07 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Operation modes:	2-way stereo/mono
Input:	Mono/stereo
Input impedance:	10/20 kohms (unb./bal.)
Output:	Mono/stereo
Output impedance:	300/150 kohms (unb./bal.)
In/out connectors:	XLR
S/N ratio:	>100 dB
THD:	0.05%
Input gain:	-~ to +6 dB
Ouptut gain:	-~ to +12 dB
Low cut:	30 Hz, -3 dB
Phase adjustment:	0-180°
Dimensions (W x D x H):	483 x 147 x 46 mm