

OMNITRONIC XO-34 Active crossover

High-quality stereo crossover

Art. No.: 10355635

GTIN: 4026397233308



The article is no longer in our assortment.

Features:

- 2-way/3-way stereo or 4-way mono operation possible
- 24 dB octave slope
- Crossover frequency control on the front panel
- Frequency range of crossover frequency 450 Hz - 9 kHz switchable to 45 - 900 Hz
- Individual output level controls for all bands
- Individual output mutes for easy band adjustment
- Phase invert control
- Low Cut switch
- XLR in and outputs
- Illuminated switches for secure operation in dark environments
- Rack installation

Logistic

EAN / GTIN: 4026397233308

Weight: 2,70 kg

Length: 0.54 m

Width: 0.20 m

Height: 0.08 m

Technical specifications:

| | |
|--------------------|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 10,00 W |
| Dimensions: | Width: 48,3 cm Depth: 14,7 cm Height: 4,45 cm |
| Weight: | 2,25 kg |
| Slope: | 24 dB / octave |
| Operation modes: | 2/3-way stereo or 4-way mono |

| | |
|-------------------------|---------------------------|
| Input: | Mono/stereo |
| Input impedance: | 10/20 kohms (unb./bal.) |
| Output: | Mono/stereo |
| Output impedance: | 300/150 kohms (unb./bal.) |
| In/Out connectors: | XLR |
| S/N ratio: | >100 dB |
| Xover frequency range: | 45-9000 Hz |
| THD: | 0.05% |
| Crosstalk: | >80 dB, -3 dB |
| Input gain: | -- to +6 dB |
| Output gain: | -- to +12 dB |
| Low Cut: | 30 Hz, -3 dB |
| Dimensions (W x D x H): | 483 x 147 x 46 mm |