

OMNITRONIC LXO-23 Active Crossover

High-quality active stereo crossover with limiter

Art. No.: 10355640

GTIN: 4026397433654



The article is no longer in our assortment.

Features:

- 2-way stereo or 3-way mono operation possible
- Limiter adjustable from -40 to 22 dB
- 24 dB octave slope
- Crossover frequency control on the front panel
- Frequency range of crossover frequency 450 Hz - 9 kHz switchable to 45 - 900 Hz
- Individual output level controls for all bands
- Individual output mutes for easy band adjustment
- Phase invert control
- Low cut switch
- XLR inputs and outputs
- Illuminated switches for secure operation in dark environments
- Rack installation
- (19") 48.3 cm rack installation 1 U

Logistic

EAN / GTIN: 4026397433654

Weight: 2,65 kg

Length: 0.54 m

Width: 0.20 m

Height: 0.08 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	10,00 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Frequency range:	45 - 9000 Hz
Housing design:	(19") 48.3 cm rack installation 1 U

Dimensions:	Width: 48,3 cm Depth: 14,7 cm Height: 4,45 cm
Weight:	2,30 kg
Limiter:	-40-22 dBu
Slope:	24 dB / octave
Operation modes:	2-way stereo or 3-way mono
Input:	Mono/stereo
Input impedance:	10/20 kohms (unb./bal.)
Output:	Mono/stereo
Output impedance:	300/150 kohms (unb./bal.)
In/Out connectors:	XLR
S/N ratio:	>100 dB
THD:	0.05%
Crosstalk:	>80 dB, -3 dB
Input gain:	-- to +6 dB
Output gain:	-- to +12 dB
Low Cut:	30 Hz, -3 dB
Phase adjustment:	0-180°