

OMNITRONIC XPA-350 MK2 Amplifier

Class AB PA amplifier with limiter, 2 x 175 W RMS (4 ohms), 2 x 130 W RMS (8 ohms)

Art. No.: 10451001

GTIN: 4026397730760



List price: 236.81 €

incl. 19% VAT.

Features:

- 2 level controls
- Signal inputs via XLR or RCA connectors
- Speaker outputs via lockable speaker jacks and pairs of screw terminals
- Class AB circuitry
- Highly efficient Air flow from front to rear
- The device is cooled by temperature-controlled fan
- (19") 48.3 cm rack installation 2 U
- For application areas such as: Clubs/dancing school; Installation; mobile use; mobile djs / entertainer; restaurants, bars and hotels; Rental; sports centres/gyms; Band/rehearsal room

Package contents

- 1 x amplifier, 1 x power cord, 4 x foot, 1 x user manual

Logistic

EAN / GTIN: 4026397730760

Weight: 8,75 kg

Length: 0.55 m

Width: 0.43 m

Height: 0.14 m

Technical specifications:

| | |
|--------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 245 W 1/8 power |
| Protection class: | Protection class I |
| Output power: | 2 x 175 W RMS (4 ohms) 2 x 130 W RMS (8 ohms) 350 W RMS bridged (8 ohms) |

| | |
|--------------------|---|
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Cable length: | 1 m detachable |
| Fuse: | 5 x 20 mm, F 8 A Fuse serviceable |
| Frequency range: | 20 - 20000 Hz |
| S/N ratio: | >95 dB |
| THD: | <0,5 % at 1 kHz |
| Cooling: | 1 x temperature-controlled fan , Air flow from front to rear |
| Impedance: | Input: 20 kOhm , bal. Input: 10 kOhm , unbal. |
| Gain: | 30 dB/ 1 V |
| Housing color: | Black |
| Circuitry: | Class AB |
| Slew rate: | >20 V/ μ s |
| Damping factor: | >200 |
| Control elements: | Power switch, level control per channel, mode switch (stereo/parallel/bridged) |
| Controls: | Short-circuit; overheat; DC voltage; softstart; power on/off transients; VHF; current limiting; limiter |
| Status LED: | Power, signal, clip, protect |
| Connections: | Input: line via 2 x 3-pin XLR Input: line via 2 x stereo RCA Output: speaker via 2 x speaker built-in socket (F) Output: speaker via screw terminal Output: Speaker (bridge) via 1 x speaker built-in socket (F) Output: Speaker (bridge) via screw terminal |
| Input sensitivity: | 1 V |
| Housing design: | (19") 48.3 cm rack installation 2 U |
| Dimensions: | Width: 48,3 cm Depth: 36,8 cm Height: 9,1 cm |
| Weight: | 7,65 kg |