

OMNITRONIC XPA-350 Amplifier

PA amplifier with limiter, 2 x 175 W / 4 ohms, 2 x 130 W / 8 ohms

Art. No.: 10451031

GTIN: 4026397593877



List price: 184.45 €

incl. 19% VAT.

Features:

- 2 operating modes can be selected (stereo or bridged)
- Limiter, switchable
- Speaker switch-on delay
- 2 level controls
- Each channel with LED for activated protective circuit (protect) and output meter with clip LED
- Complete protection set against short-circuit, overheat, DC voltage, power on/off transients
- Groundlift switch against humming
- Signal inputs via XLR or 6.3mm jack connectors
- Speaker outputs via lockable speaker jacks and pairs of screw terminals
- Additional Speaker plug for 8-ohm bridge operation
- Class AB circuitry
- The device is cooled by cooling fan
- (19") 48.3 cm rack installation 2 U

Logistic

EAN / GTIN: 4026397593877

Weight: 8,25 kg

Length: 0.53 m

Width: 0.42 m

Height: 0.15 m

Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	280 W 1/8 power
Output power:	2 x 175 W RMS (4 ohms) 2 x 130 W RMS (8 ohms) 350 W RMS bridged (8 ohms)
Power connection:	Mains input IEC connector (M) mounting version Power supply cord with safety plug (provided)

Frequency range:	20 - 20000 Hz
S/N ratio:	>95 dB
THD:	<0,5 % at 1 kHz
Cooling:	Cooling fan
Impedance:	Input 20 kOhm , bal. Input 10 kOhm , unbal.
Circuitry:	Class AB
Slew rate:	>20 V/ μ s
Damping factor:	>350
Control elements:	Power switch, level control per channel, groundlift selector, limiter selector, mode switch (stereo/bridged)
Controls:	Short-circuit; overheat; DC voltage; softstart; power on/off transients
Status LED:	Power, level meter, clip, bridged, protect
Connections:	Input: 2 x line via 3-pin XLR Input: 2 x line via 6.3 mm jack socket (stereo) mounting version Output: 2 x speakers via speaker built-in socket (F) Output: speakers via screw terminal Output: 1 x Speaker (bridge) via speaker built-in socket (F)
Input sensitivity:	1,4 V
Max. level:	Input: +21 dBV Input: +9 V
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm Depth: 35,4 cm Height: 8,9 cm
Weight:	7,35 kg