

OMNITRONIC DJP-604 4-channel Class D Amplifier

4-channel class D amplifier in 9.5" housing, 4 x 150 W / 4 ohms, 4 x 80 W / 8 ohms

Art. No.: 10451606

GTIN: 4026397702422



Features:

- Inputs linkable for flexible configuration
- Extremely low weight and height due to integrated switch mode power supply
- Level control per channel
- Rugged steel chassis with aluminum front panel
- Desktop console housing
- (19") 48.3 cm rack installation possible
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

Logistic

EAN / GTIN: 4026397702422

Weight: 2,84 kg

Length: 0.34 m

Width: 0.29 m

Height: 0.08 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	185 W 1/8 power
Output power:	4 x 150 W RMS (4 ohms) 4 x 80 W RMS (8 ohms)
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Frequency range:	20 - 20.000 Hz
S/N ratio:	>105 dB
Impedance:	Input: 20 kOhm , bal. Input: 10 kOhm , unbal.

Housing color:	Black
Circuitry:	Class D
Slew rate:	20 V/μs
Damping factor:	>300
Control elements:	Power switch, level control per channel
Controls:	Softstart; short-circuit; overheat; overload; VHF; DC voltage
Status LED:	Power, signal, clip
Connections:	Input: line via 4 x screw plug-in terminal Output: speaker via 4 x screw plug-in terminal
Material:	Metal
Housing design:	Desktop console housing (19") 48.3 cm rack installation possible
Dimensions:	Width: 21.4 cm Depth: 26.5 cm Height: 4.4 cm
Weight:	2.46 kg

Scope of delivery:

- 1 x user manual
- 1 x amplifier
- 4 x foot
- 6 x angle
- 8 x screw
- 1 x power cord