

OMNITRONIC XDA-2402 Class D Amplifier

Stereo PA amplifier with SMPS, 2 x 1200 W / 4 ohms, 2 x 880 W / 8 ohms

Art. No.: 10451636

GTIN: 4026397580150



List price: 522.41 €

incl. 19% VAT.

Features:

- Stereo PA amplifier with class D circuitry
- Low weight and height due to integrated switch mode power supply
- Speaker switch-on delay and auto limiters
- 2 level controls
- LEDs for activated protective circuit, limiter, signal, and power
- Complete protection set against short-circuit, overheat, DC voltage, power on/off transients, soft start
- Ground lift switch against humming
- Electronically balanced inputs via XLR mounting jacks with feed-through output
- Speaker outputs via lockable speaker jacks
- The device is cooled by cooling fan
- (19") 48.3 cm rack installation 1 U

Logistic

EAN / GTIN: 4026397580150

Weight: 7,75 kg

Length: 0.59 m

Width: 0.47 m

Height: 0.07 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	465 W 1/8 power
Output power:	2 x 880 W RMS (8 ohms) 2 x 1200 W RMS (4 ohms)
Power connection:	Mains input P-Con (blue), mounting version Power supply cord with safety plug (provided)
Frequency range:	30 - 20000 Hz

S/N ratio:	>100 dB
THD:	<0,02 % at 1 kHz
Cooling:	Cooling fan
Impedance:	Input 20 kOhm , bal. Input 10 kOhm , unbal.
Circuitry:	Class D
Control elements:	Power switch, level control per channel, groundlift selector
Controls:	Short-circuit; overheat; DC voltage; power on/off transients; softstart; power on/off transient; limiter
Status LED:	Power, signal, limit, protect
Connections:	Input: 2 x line via 3-pin XLR Link: 2 x line via 3-pin XLR Output: 2 x speakers via speaker built-in socket (F)
Input sensitivity:	1,25 V
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Width: 48,3 cm Depth: 35,5 cm Height: 4,45 cm
Weight:	6,40 kg