

PSSO®

DDA-2700 MK2 2-channel Amplifier

Class TD stereo PA amplifier with SMPS, 2 x 1350 W RMS (4 ohms), 2 x 1000 W RMS (8 ohms)

Art. No.: 10451688
GTIN: 4026397747171



PSSO®

DDA-2700 MK2 2-channel Amplifier

Class TD stereo PA amplifier with SMPS, 2 x 1350 W RMS (4 ohms), 2 x 1000 W RMS (8 ohms)

Art. No.: 10451688
GTIN: 4026397747171

Features:

- Low weight and height due to integrated switch mode power supply
- Reliable power amp with high impulse stability for a wide range of applications (e.g. compact PAs, multi-way PAs, concerts)
- Limiter and speaker switch-on delay
- 3 operating modes can be selected (stereo, parallel or bridged)
- 2 calibrated level controls for precise level adjustment
- Input sensitivity adjustable
- LED VU meter and LEDs for activated protective circuit (protect) and overload (clip) per channel
- Electronically balanced inputs via XLR mounting jacks, with XLR feed-through outputs
- Speaker outputs via lockable speaker jacks and pairs of screw terminals
- Rugged steel chassis with aluminum front panel
- (19") 48.3 cm rack installation 2 U
- Highly efficient air flow from front to rear
- The device is cooled by temperature-controlled fan